



Slovar in kratice ITIL®

slovenščina

Ta slovar lahko prosto vzamete s spleta. O pogojih licenciranja preberite na <http://www.iti-officialsite.com/InternationalActivities/TranslatedGlossaries.aspx>

Zahvala

Zahvaljujemo se avtorjema prvega slovarja ITIL (maj 2007) g. Ashleyu Hanna (HP) in Stuartu Rance (HP) ter g. Ashleyu Hanna za posodobitev slovarja v juliju 2011.

Zahvaljujemo se tudi vsem tistim sodelavcem, ki so prispevali izdajam ITIL 2007 in 2011. Popoln seznam zahval je na voljo na www.itsil-officialsite.com/Publications/PublicationAcknowledgements.aspx.

Zahvaljujemo se prevajalski skupini Združenja za upravljanje storitev IT, ki je pripravila slovenske prevode izrazov:

Anton Žvanut (ADD d.o.o. Ljubljana)
Beno Oražem (SRC d.o.o.)
Igor Mlakar (Smart Com d.o.o.)
Katja Kous (Univerza v Mariboru, Fakulteta za elektrotehniko, računalništvo in informatiko)
Rok Dolinšek (Troia d.o.o.)
Tomaž Krajnc (Elektro Ljubljana, d.d.)
Tomo Jarc (Univerza v Ljubljani)

Posebej se zahvaljujemo vsem pregledovalcem za koristne pripombe in predloge:

Aleš Groznik
Andrej Erzetič
Boštjan Kežmah
Branko Dolenc
Marjan Posedi
Marjan Schaubach
Tomaž Hiti
Vladimir Zorc

#	Angleški pojem	Slovenski pojem	Angleški opis
1	acceptance	prevzem	Formal agreement that an IT service, process, plan or other deliverable is complete, accurate, reliable and meets its specified requirements. Acceptance is usually preceded by change evaluation or testing and is often required before proceeding to the next stage of a project or process. <i>See also</i> service acceptance criteria.
2	access management	upravljanje z uporabniškimi dovoljenji	<i>(ITIL Service Operation)</i> The process responsible for allowing users to make use of IT services, data or other assets. Access management helps to protect the confidentiality, integrity and availability of assets by ensuring that only authorized users are able to access or modify them. Access management implements the policies of information security management and is sometimes referred to as rights management or identity management.
3	account manager	skrbnik strank	<i>(ITIL Service Strategy)</i> A role that is very similar to that of the business relationship manager, but includes more commercial aspects. Most commonly used by Type III service providers when dealing with external customers.
4	accounting	računovodstvo	<i>(ITIL Service Strategy)</i> The process responsible for identifying the actual costs of delivering IT services, comparing these with budgeted costs, and managing variance from the budget.
5	accounting period	računovodsko obdobje	<i>(ITIL Service Strategy)</i> A period of time (usually one year) for which budgets, charges, depreciation and other financial calculations are made. <i>See also</i> financial year.
6	accredited	akreditiran	Officially authorized to carry out a role. For example, an accredited body may be authorized to provide training or to conduct audits.
7	active monitoring	aktivno spremljanje	<i>(ITIL Service Operation)</i> Monitoring of a configuration item or an IT service that uses automated regular checks to discover the current status. <i>See also</i> passive monitoring.
8	activity	aktivnost	A set of actions designed to achieve a particular result. Activities are usually defined as part of processes or plans, and are documented in procedures.
9	agreed service time (AST)	urnik storitve	<i>(ITIL Service Design)</i> A synonym for service hours, commonly used in formal calculations of availability. <i>See also</i> downtime.
10	agreement	dogovor	A document that describes a formal understanding between two or more parties. An agreement is not legally binding, unless it forms part of a contract. <i>See also</i> operational level agreement; service level agreement.
11	alert	preplah	<i>(ITIL Service Operation)</i> A notification that a threshold has been reached, something has changed, or a failure has occurred. Alerts are often created and managed by system management tools and are managed by the event management process.
12	analytical modelling	analitično modeliranje	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> <i>(ITIL Service Strategy)</i> A technique that uses mathematical models to predict the behaviour of IT services or other configuration items. Analytical models are commonly used in capacity management and availability management. <i>See also</i> modelling; simulation modelling.
13	application	uporabniški program	Software that provides functions which are required by an IT service. Each application may be part of more than one IT service. An application runs on one or more servers or clients. <i>See also</i> application management; application portfolio.
14	application management	upravljanje uporabniških programov	<i>(ITIL Service Operation)</i> The function responsible for managing applications throughout their lifecycle.
15	application portfolio	portfelj uporabniških programov	<i>(ITIL Service Design)</i> A database or structured document used to manage applications throughout their lifecycle. The application portfolio contains key attributes of all applications. The application portfolio is sometimes implemented as part of the service portfolio, or as part of the configuration management system.

#	Angleški pojem	Slovenski pojem	Angleški opis
16	application service provider (ASP)	ponudnik programskih storitev	<i>(ITIL Service Design)</i> An external service provider that provides IT services using applications running at the service provider's premises. Users access the applications by network connections to the service provider.
17	application sizing	analiza potreb uporabniškega programa	<i>(ITIL Service Design)</i> The activity responsible for understanding the resource requirements needed to support a new application, or a major change to an existing application. Application sizing helps to ensure that the IT service can meet its agreed service level targets for capacity and performance.
18	architecture	arhitektura	<i>(ITIL Service Design)</i> The structure of a system or IT service, including the relationships of components to each other and to the environment they are in. Architecture also includes the standards and guidelines that guide the design and evolution of the system.
19	assembly	sestavljanka	<i>(ITIL Service Transition)</i> A configuration item that is made up of a number of other CIs. For example, a server CI may contain CIs for CPUs, disks, memory etc.; an IT service CI may contain many hardware, software and other CIs. <i>See also</i> build; component CI.
20	assessment	ocenjevanje	Inspection and analysis to check whether a standard or set of guidelines is being followed, that records are accurate, or that efficiency and effectiveness targets are being met. <i>See also</i> audit.
21	asset	sredstvo	<i>(ITIL Service Strategy)</i> Any resource or capability. The assets of a service provider include anything that could contribute to the delivery of a service. Assets can be one of the following types: management, organization, process, knowledge, people, information, applications, infrastructure or financial capital. <i>See also</i> customer asset; service asset; strategic asset.
22	asset management	upravljanje sredstev	<i>(ITIL Service Transition)</i> A generic activity or process responsible for tracking and reporting the value and ownership of assets throughout their lifecycle. <i>See also</i> service asset and configuration management; fixed asset management; software asset management.
23	asset register	register sredstev	<i>(ITIL Service Transition)</i> A list of fixed assets that includes their ownership and value. <i>See also</i> fixed asset management.
24	asset specificity	posebnosti sredstva	<i>(ITIL Service Strategy)</i> One or more attributes of an asset that make it particularly useful for a given purpose. Asset specificity may limit the use of the asset for other purposes.
25	attribute	atribut	<i>(ITIL Service Transition)</i> A piece of information about a configuration item. Examples are name, location, version number and cost. Attributes of CIs are recorded in a configuration management database (CMDB) and maintained as part of a configuration management system (CMS). <i>See also</i> relationship; configuration management system.
26	audit	presoja	Formal inspection and verification to check whether a standard or set of guidelines is being followed, that records are accurate, or that efficiency and effectiveness targets are being met. An audit may be carried out by internal or external groups. <i>See also</i> assessment; certification.
27	authority matrix	matrika odgovornosti	<i>See</i> RACI.
28	automatic call distribution (ACD)	samodejno razporejanje klicev	<i>(ITIL Service Operation)</i> Use of information technology to direct an incoming telephone call to the most appropriate person in the shortest possible time. ACD is sometimes called automated call distribution.
29	availability	razpoložljivost	<i>(ITIL Service Design)</i> Ability of an IT service or other configuration item to perform its agreed function when required. Availability is determined by reliability, maintainability, serviceability, performance and security. Availability is usually calculated as a percentage. This calculation is often based on agreed service time and downtime. It is best practice to calculate availability of an IT service using measurements of the business output.

#	Angleški pojem	Slovenski pojem	Angleški opis
30	availability management (AM)	upravljanje z razpoložljivostjo	<i>(ITIL Service Design)</i> The process responsible for ensuring that IT services meet the current and future availability needs of the business in a cost-effective and timely manner. Availability management defines, analyses, plans, measures and improves all aspects of the availability of IT services, and ensures that all IT infrastructures, processes, tools, roles etc. are appropriate for the agreed service level targets for availability. <i>See also</i> availability management information system.
31	availability management information system (AMIS)	informacijski sistem za upravljanje z razpoložljivostjo	<i>(ITIL Service Design)</i> A set of tools, data and information that is used to support availability management. <i>See also</i> service knowledge management system.
32	availability plan	načrt razpoložljivosti	<i>(ITIL Service Design)</i> A plan to ensure that existing and future availability requirements for IT services can be provided cost-effectively.
33	back-out	povrnitev stanja	<i>(ITIL Service Transition)</i> An activity that restores a service or other configuration item to a previous baseline. Back-out is used as a form of remediation when a change or release is not successful.
34	backup	varnostno kopiranje	<i>(ITIL Service Design)</i> <i>(ITIL Service Operation)</i> Copying data to protect against loss of integrity or availability of the original.
35	balanced scorecard	ključni kazalniki uspešnosti	<i>(ITIL Continual Service Improvement)</i> A management tool developed by Drs Robert Kaplan (Harvard Business School) and David Norton. A balanced scorecard enables a strategy to be broken down into key performance indicators. Performance against the KPIs is used to demonstrate how well the strategy is being achieved. A balanced scorecard has four major areas, each of which has a small number of KPIs. The same four areas are considered at different levels of detail throughout the organization.
36	baseline	izhodiščno stanje	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Transition)</i> A snapshot that is used as a reference point. Many snapshots may be taken and recorded over time but only some will be used as baselines. For example: An ITSM baseline can be used as a starting point to measure the effect of a service improvement plan A performance baseline can be used to measure changes in performance over the lifetime of an IT service A configuration baseline can be used as part of a back-out plan to enable the IT infrastructure to be restored to a known configuration if a change or release fails. <i>See also</i> benchmark.
37	benchmark	preizkusni rezultat	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Transition)</i> A baseline that is used to compare related data sets as part of a benchmarking exercise. For example, a recent snapshot of a process can be compared to a previous baseline of that process, or a current baseline can be compared to industry data or best practice. <i>See also</i> benchmarking; baseline.
38	benchmarking	primerjalna presoja	<i>(ITIL Continual Service Improvement)</i> The process responsible for comparing a benchmark with related data sets such as a more recent snapshot, industry data or best practice. The term is also used to mean creating a series of benchmarks over time, and comparing the results to measure progress or improvement. This process is not described in detail within the core ITIL publications.
39	Best Management Practice (BMP)	najboljša praksa upravljanja	The Best Management Practice portfolio is owned by the Cabinet Office, part of HM Government. Formerly owned by CCTA and then OGC, the BMP functions moved to the Cabinet Office in June 2010. The BMP portfolio includes guidance on IT service management and project, programme, risk, portfolio and value management. There is also a management maturity model as well as related glossaries of terms.
40	best practice	dobra praksa	Proven activities or processes that have been successfully used by multiple organizations. ITIL is an example of best practice.
41	billing	zaračunavanje	<i>(ITIL Service Strategy)</i> Part of the charging process. Billing is the activity responsible for producing an invoice or a bill and recovering the money from customers. <i>See also</i> pricing.
42	brainstorming	viharjenje idej	<i>(ITIL Service Design)</i> <i>(ITIL Service Operation)</i> A technique that helps a team to generate ideas. Ideas are not reviewed during the brainstorming session, but at a later stage. Brainstorming is often used by problem management to identify possible causes.

#	Angleški pojem	Slovenski pojem	Angleški opis
43	British Standards Institution (BSI)	British Standards Institution (BSI)	The UK national standards body, responsible for creating and maintaining British standards. See www.bsi-global.com for more information. <i>See also</i> International Organization for Standardization.
44	budget	proračun	A list of all the money an organization or business unit plans to receive, and plans to pay out, over a specified period of time. <i>See also</i> budgeting; planning.
45	budgeting	predračunavanje	The activity of predicting and controlling the spending of money. Budgeting consists of a periodic negotiation cycle to set future budgets (usually annual) and the day-to-day monitoring and adjusting of current budgets.
46	build	postavitev	<i>(ITIL Service Transition)</i> The activity of assembling a number of configuration items to create part of an IT service. The term is also used to refer to a release that is authorized for distribution – for example, server build or laptop build. <i>See also</i> configuration baseline.
47	build environment	okolje postavitve	<i>(ITIL Service Transition)</i> A controlled environment where applications, IT services and other builds are assembled prior to being moved into a test or live environment.
48	business	področje poslovanja	<i>(ITIL Service Strategy)</i> An overall corporate entity or organization formed of a number of business units. In the context of ITSM, the term includes public sector and not-for-profit organizations, as well as companies. An IT service provider provides IT services to a customer within a business. The IT service provider may be part of the same business as its customer (internal service provider), or part of another business (external service provider).
49	business capacity management	upravljanje zmogljivosti poslovanja	<i>(ITIL Continual Service Improvement) (ITIL Service Design)</i> In the context of ITSM, business capacity management is the sub-process of capacity management responsible for understanding future business requirements for use in the capacity plan. <i>See also</i> service capacity management; component capacity management.
50	business case	poslovni primer	<i>(ITIL Service Strategy)</i> Justification for a significant item of expenditure. The business case includes information about costs, benefits, options, issues, risks and possible problems. <i>See also</i> cost benefit analysis.
51	business continuity management (BCM)	upravljanje neprekinjenosti poslovanja	<i>(ITIL Service Design)</i> The business process responsible for managing risks that could seriously affect the business. Business continuity management safeguards the interests of key stakeholders, reputation, brand and value-creating activities. The process involves reducing risks to an acceptable level and planning for the recovery of business processes should a disruption to the business occur. Business continuity management sets the objectives, scope and requirements for IT service continuity management.
52	business continuity plan (BCP)	načrt za neprekinjenost poslovanja	<i>(ITIL Service Design)</i> A plan defining the steps required to restore business processes following a disruption. The plan also identifies the triggers for invocation, people to be involved, communications etc. IT service continuity plans form a significant part of business continuity plans.
53	business customer	poslovna stranka	<i>(ITIL Service Strategy)</i> A recipient of a product or a service from the business. For example, if the business is a car manufacturer, then the business customer is someone who buys a car.
54	business impact analysis (BIA)	analiza vpliva na poslovanje	<i>(ITIL Service Strategy)</i> Business impact analysis is the activity in business continuity management that identifies vital business functions and their dependencies. These dependencies may include suppliers, people, other business processes, IT services etc. Business impact analysis defines the recovery requirements for IT services. These requirements include recovery time objectives, recovery point objectives and minimum service level targets for each IT service.
55	business objective	poslovni cilj	<i>(ITIL Service Strategy)</i> The objective of a business process, or of the business as a whole. Business objectives support the business vision, provide guidance for the IT strategy, and are often supported by IT services.

#	Angleški pojem	Slovenski pojem	Angleški opis
56	business operations	poslovanje (običajno)	<i>(ITIL Service Strategy)</i> The day-to-day execution, monitoring and management of business processes.
57	business perspective	poslovni vidik	<i>(ITIL Continual Service Improvement)</i> An understanding of the service provider and IT services from the point of view of the business, and an understanding of the business from the point of view of the service provider.
58	business process	poslovni proces	A process that is owned and carried out by the business. A business process contributes to the delivery of a product or service to a business customer. For example, a retailer may have a purchasing process that helps to deliver services to its business customers. Many business processes rely on IT services.
59	business relationship management	upravljanje poslovnih odnosov	<i>(ITIL Service Strategy)</i> The process responsible for maintaining a positive relationship with customers. Business relationship management identifies customer needs and ensures that the service provider is able to meet these needs with an appropriate catalogue of services. This process has strong links with service level management.
60	business relationship manager (BRM)	skrbnik poslovnih odnosov	<i>(ITIL Service Strategy)</i> A role responsible for maintaining the relationship with one or more customers. This role is often combined with the service level manager role.
61	business service	poslovna storitev	A service that is delivered to business customers by business units. For example, delivery of financial services to customers of a bank, or goods to the customers of a retail store. Successful delivery of business services often depends on one or more IT services. A business service may consist almost entirely of an IT service – for example, an online banking service or an external website where product orders can be placed by business customers. <i>See also</i> customer-facing service.
62	business service management	upravljanje poslovnih storitev	The management of business services delivered to business customers. Business service management is performed by business units.
63	business unit	poslovna enota	<i>(ITIL Service Strategy)</i> A segment of the business that has its own plans, metrics, income and costs. Each business unit owns assets and uses these to create value for customers in the form of goods and services.
64	call	klic	<i>(ITIL Service Operation)</i> A telephone call to the service desk from a user. A call could result in an incident or a service request being logged.
65	call centre	klicni center	<i>(ITIL Service Operation)</i> An organization or business unit that handles large numbers of incoming and outgoing telephone calls. <i>See also</i> service desk.
66	call type	vrsta klica	<i>(ITIL Service Operation)</i> A category that is used to distinguish incoming requests to a service desk. Common call types are incident, service request and complaint.
67	capability	zmožnost	<i>(ITIL Service Strategy)</i> The ability of an organization, person, process, application, IT service or other configuration item to carry out an activity. Capabilities are intangible assets of an organization. <i>See also</i> resource.
68	Capability Maturity Model Integration (CMMI)	zmožnostno zrelostni model	<i>(ITIL Continual Service Improvement)</i> A process improvement approach developed by the Software Engineering Institute (SEI) of Carnegie Mellon University, US. CMMI provides organizations with the essential elements of effective processes. It can be used to guide process improvement across a project, a division or an entire organization. CMMI helps integrate traditionally separate organizational functions, set process improvement goals and priorities, provide guidance for quality processes, and provide a point of reference for appraising current processes. <i>See</i> www.sei.cmu.edu/cmml for more information. <i>See also</i> maturity.
69	capacity	zmogljivost	<i>(ITIL Service Design)</i> The maximum throughput that a configuration item or IT service can deliver. For some types of CI, capacity may be the size or volume – for example, a disk drive.

#	Angleški pojem	Slovenski pojem	Angleški opis
70	capacity management	upravljanje zmogljivosti	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> The process responsible for ensuring that the capacity of IT services and the IT infrastructure is able to meet agreed capacity- and performance-related requirements in a cost-effective and timely manner. Capacity management considers all resources required to deliver an IT service, and is concerned with meeting both the current and future capacity and performance needs of the business. Capacity management includes three sub-processes: business capacity management, service capacity management, and component capacity management. <i>See also</i> capacity management information system.
71	capacity management information system (CMIS)	informatijski sistem za upravljanje zmogljivosti	<i>(ITIL Service Design)</i> A set of tools, data and information that is used to support capacity management. <i>See also</i> service knowledge management system.
72	capacity plan	načrt zmogljivosti	<i>(ITIL Service Design)</i> A plan used to manage the resources required to deliver IT services. The plan contains details of current and historic usage of IT services and components, and any issues that need to be addressed (including related improvement activities). The plan also contains scenarios for different predictions of business demand and costed options to deliver the agreed service level targets.
73	capacity planning	načrtovanje zmogljivosti	<i>(ITIL Service Design)</i> The activity within capacity management responsible for creating a capacity plan.
74	capital budgeting	investicijsko predračunavanje	<i>(ITIL Service Strategy)</i> The present commitment of funds in order to receive a return in the future in the form of additional cash inflows or reduced cash outflows.
75	capital cost	stroški kapitala	<i>(ITIL Service Strategy)</i> The cost of purchasing something that will become a financial asset – for example, computer equipment and buildings. The value of the asset depreciates over multiple accounting periods. <i>See also</i> operational cost.
76	capital expenditure (CAPEX)	investicijski stroški	<i>See</i> capital cost.
77	capitalization	kapitalizacija	<i>(ITIL Service Strategy)</i> Identifying major cost as capital, even though no asset is purchased. This is done to spread the impact of the cost over multiple accounting periods. The most common example of this is software development, or purchase of a software licence.
78	category	kategorija	A named group of things that have something in common. Categories are used to group similar things together. For example, cost types are used to group similar types of cost. Incident categories are used to group similar types of incident, while CI types are used to group similar types of configuration item.
79	certification	certificiranje	Issuing a certificate to confirm compliance to a standard. Certification includes a formal audit by an independent and accredited body. The term is also used to mean awarding a certificate to provide evidence that a person has achieved a qualification.
80	change	sprememba	<i>(ITIL Service Transition)</i> The addition, modification or removal of anything that could have an effect on IT services. The scope should include changes to all architectures, processes, tools, metrics and documentation, as well as changes to IT services and other configuration items.
81	change advisory board (CAB)	odbor za spremembe	<i>(ITIL Service Transition)</i> A group of people that support the assessment, prioritization, authorization and scheduling of changes. A change advisory board is usually made up of representatives from: all areas within the IT service provider; the business; and third parties such as suppliers.
82	change evaluation	ovrednotenje spremembe	<i>(ITIL Service Transition)</i> The process responsible for formal assessment of a new or changed IT service to ensure that risks have been managed and to help determine whether to authorize the change.
83	change history	zgodovina spremembe	<i>(ITIL Service Transition)</i> Information about all changes made to a configuration item during its life. Change history consists of all those change records that apply to the CI.
84	change management	upravljanje sprememb	<i>(ITIL Service Transition)</i> The process responsible for controlling the lifecycle of all changes, enabling beneficial changes to be made with minimum disruption to IT services.

#	Angleški pojem	Slovenski pojem	Angleški opis
85	change model	model sprememb	<i>(ITIL Service Transition)</i> A repeatable way of dealing with a particular category of change. A change model defines specific agreed steps that will be followed for a change of this category. Change models may be very complex with many steps that require authorization (e.g. major software release) or may be very simple with no requirement for authorization (e.g. password reset). <i>See also</i> change advisory board; standard change.
86	change proposal	predlog spremembe	<i>(ITIL Service Strategy)</i> <i>(ITIL Service Transition)</i> A document that includes a high level description of a potential service introduction or significant change, along with a corresponding business case and an expected implementation schedule. Change proposals are normally created by the service portfolio management process and are passed to change management for authorization. Change management will review the potential impact on other services, on shared resources, and on the overall change schedule. Once the change proposal has been authorized, service portfolio management will charter the service.
87	change record	zapis o spremembi	<i>(ITIL Service Transition)</i> A record containing the details of a change. Each change record documents the lifecycle of a single change. A change record is created for every request for change that is received, even those that are subsequently rejected. Change records should reference the configuration items that are affected by the change. Change records may be stored in the configuration management system, or elsewhere in the service knowledge management system.
88	change request	zahtevek za spremembo	<i>See</i> request for change.
89	change schedule	razpored sprememb	<i>(ITIL Service Transition)</i> A document that lists all authorized changes and their planned implementation dates, as well as the estimated dates of longer-term changes. A change schedule is sometimes called a forward schedule of change, even though it also contains information about changes that have already been implemented.
90	change window	okno za spremembe	<i>(ITIL Service Transition)</i> A regular, agreed time when changes or releases may be implemented with minimal impact on services. Change windows are usually documented in service level agreements.
91	chargeable item	obračunski element	<i>(ITIL Service Strategy)</i> A deliverable of an IT service that is used in calculating charges to customers (for example, number of transactions, number of desktop PCs).
92	charging	obračunavanje	<i>(ITIL Service Strategy)</i> Requiring payment for IT services. Charging for IT services is optional, and many organizations choose to treat their IT service provider as a cost centre. <i>See also</i> charging process; charging policy.
93	charging policy	politika obračunavanja	<i>(ITIL Service Strategy)</i> A policy specifying the objective of the charging process and the way in which charges will be calculated. <i>See also</i> cost.
94	charging process	obračunski proces	<i>(ITIL Service Strategy)</i> The process responsible for deciding how much customers should pay (pricing) and recovering money from them (billing). This process is not described in detail within the core ITIL publications.
95	charter	vzpostavitevni dokument, odobritev	<i>(ITIL Service Strategy)</i> A document that contains details of a new service, a significant change or other significant project. Charters are typically authorized by service portfolio management or by a project management office. The term charter is also used to describe the act of authorizing the work required to complete the service change or project. <i>See also</i> change proposal; service charter; project portfolio.
96	chronological analysis	časovna analiza	<i>(ITIL Service Operation)</i> A technique used to help identify possible causes of problems. All available data about the problem is collected and sorted by date and time to provide a detailed timeline. This can make it possible to identify which events may have been triggered by others.
97	CI type	vrsta elementa konfiguracije	<i>(ITIL Service Transition)</i> A category that is used to classify configuration items. The CI type identifies the required attributes and relationships for a configuration record. Common CI types include hardware, document, user etc.

#	Angleški pojem	Slovenski pojem	Angleški opis
98	classification	razvrstitev	The act of assigning a category to something. Classification is used to ensure consistent management and reporting. Configuration items, incidents, problems, changes etc. are usually classified.
99	client	odjemalec; stranka	A generic term that means a customer, the business or a business customer. For example, client manager may be used as a synonym for business relationship manager. The term is also used to mean: A computer that is used directly by a user – for example, a PC, a handheld computer or a work station The part of a client server application that the user directly interfaces with – for example, an email client.
100	closed	zaključeno	(<i>ITIL Service Operation</i>) The final status in the lifecycle of an incident, problem, change etc. When the status is closed, no further action is taken.
101	closure	zaključek	(<i>ITIL Service Operation</i>) The act of changing the status of an incident, problem, change etc. to closed.
102	COBIT	COBIT	(<i>ITIL Continual Service Improvement</i>) Control Objectives for Information and related Technology (COBIT) provides guidance and best practice for the management of IT processes. COBIT is published by ISACA in conjunction with the IT Governance Institute (ITGI). See www.isaca.org for more information.
103	code of practice	kodeks ravnanja	A guideline published by a public body or a standards organization, such as ISO or BSI. Many standards consist of a code of practice and a specification. The code of practice describes recommended best practice.
104	cold standby	hladna pripravljenost	See gradual recovery.
105	commercial off the shelf (COTS)	gotovi izdelek	(<i>ITIL Service Design</i>) Pre-existing application software or middleware that can be purchased from a third party.
106	compliance	skladnost	Ensuring that a standard or set of guidelines is followed, or that proper, consistent accounting or other practices are being employed.
107	component	(sestavni) del	A general term that is used to mean one part of something more complex. For example, a computer system may be a component of an IT service; an application may be a component of a release unit. Components that need to be managed should be configuration items.
108	component capacity management (CCM)	upravljanje zmogljivosti (sestavnih) delov	(<i>ITIL Continual Service Improvement</i>) (<i>ITIL Service Design</i>) The sub-process of capacity management responsible for understanding the capacity, utilization and performance of configuration items. Data is collected, recorded and analysed for use in the capacity plan. See also business capacity management; service capacity management.
109	component CI	(sestavni) del elementa konfiguracije	(<i>ITIL Service Transition</i>) A configuration item that is part of an assembly. For example, a CPU or memory CI may be part of a server CI.
110	component failure impact analysis (CFIA)	analiza posledic odpovedi (sestavnega) dela	(<i>ITIL Service Design</i>) A technique that helps to identify the impact of configuration item failure on IT services and the business. A matrix is created with IT services on one axis and CIs on the other. This enables the identification of critical CIs (that could cause the failure of multiple IT services) and fragile IT services (that have multiple single points of failure).
111	computer telephony integration (CTI)	povezava računalnika in telefona	(<i>ITIL Service Operation</i>) Computer telephony integration is a general term covering any kind of integration between computers and telephone systems. It is most commonly used to refer to systems where an application displays detailed screens relating to incoming or outgoing telephone calls. See also automatic call distribution; interactive voice response.
112	concurrency	število sočasnih uporabnikov	A measure of the number of users engaged in the same operation at the same time.
113	confidentiality	zaupnost	(<i>ITIL Service Design</i>) A security principle that requires that data should only be accessed by authorized people.
114	configuration	konfiguracija	(<i>ITIL Service Transition</i>) A generic term used to describe a group of configuration items that work together to deliver an IT service, or a recognizable part of an IT service. Configuration is also used to describe the parameter settings for one or more configuration items.

#	Angleški pojem	Slovenski pojem	Angleški opis
115	configuration baseline	izhodiščno stanje konfiguracije	<i>(ITIL Service Transition)</i> The baseline of a configuration that has been formally agreed and is managed through the change management process. A configuration baseline is used as a basis for future builds, releases and changes.
116	configuration control	nadzor konfiguracije	<i>(ITIL Service Transition)</i> The activity responsible for ensuring that adding, modifying or removing a configuration item is properly managed – for example, by submitting a request for change or service request.
117	configuration identification	prepoznavanje konfiguracije	<i>(ITIL Service Transition)</i> The activity responsible for collecting information about configuration items and their relationships, and loading this information into the configuration management database. Configuration identification is also responsible for labelling the configuration items themselves, so that the corresponding configuration records can be found.
118	configuration item (CI)	element konfiguracije	<i>(ITIL Service Transition)</i> Any component or other service asset that needs to be managed in order to deliver an IT service. Information about each configuration item is recorded in a configuration record within the configuration management system and is maintained throughout its lifecycle by service asset and configuration management. Configuration items are under the control of change management. They typically include IT services, hardware, software, buildings, people and formal documentation such as process documentation and service level agreements.
119	configuration management	upravljanje konfiguracije	See service asset and configuration management.
120	configuration management database (CMDB)	podatkovna zbirka o konfiguracijah	<i>(ITIL Service Transition)</i> A database used to store configuration records throughout their lifecycle. The configuration management system maintains one or more configuration management databases, and each database stores attributes of configuration items, and relationships with other configuration items.
121	configuration management system (CMS)	sistem za upravljanje konfiguracij	<i>(ITIL Service Transition)</i> A set of tools, data and information that is used to support service asset and configuration management. The CMS is part of an overall service knowledge management system and includes tools for collecting, storing, managing, updating, analysing and presenting data about all configuration items and their relationships. The CMS may also include information about incidents, problems, known errors, changes and releases. The CMS is maintained by service asset and configuration management and is used by all IT service management processes. See also configuration management database.
122	configuration record	zapis o konfiguraciji	<i>(ITIL Service Transition)</i> A record containing the details of a configuration item. Each configuration record documents the lifecycle of a single configuration item. Configuration records are stored in a configuration management database and maintained as part of a configuration management system.
123	configuration structure	zgradba konfiguracije	<i>(ITIL Service Transition)</i> The hierarchy and other relationships between all the configuration items that comprise a configuration.
124	continual service improvement (CSI)	neprestano izboljševanje storitve	<i>(ITIL Continual Service Improvement)</i> A stage in the lifecycle of a service. Continual service improvement ensures that services are aligned with changing business needs by identifying and implementing improvements to IT services that support business processes. The performance of the IT service provider is continually measured and improvements are made to processes, IT services and IT infrastructure in order to increase efficiency, effectiveness and cost effectiveness. Continual service improvement includes the seven-step improvement process. Although this process is associated with continual service improvement, most processes have activities that take place across multiple stages of the service lifecycle. See also Plan-Do-Check-Act.
125	continuous availability	neprestana razpoložljivost	<i>(ITIL Service Design)</i> An approach or design to achieve 100% availability. A continuously available IT service has no planned or unplanned downtime.

#	Angleški pojem	Slovenski pojem	Angleški opis
126	continuous operation	neprekinjeno obratovanje	<i>(ITIL Service Design)</i> An approach or design to eliminate planned downtime of an IT service. Note that individual configuration items may be down even though the IT service is available.
127	contract	pogodba	A legally binding agreement between two or more parties.
128	control	nadzor	A means of managing a risk, ensuring that a business objective is achieved or that a process is followed. Examples of control include policies, procedures, roles, RAID, door locks etc. A control is sometimes called a countermeasure or safeguard. Control also means to manage the utilization or behaviour of a configuration item, system or IT service.
129	Control Objectives for Information and related Technology	kontrolni cilji za informacijsko in sorodno tehnologijo	See COBIT.
130	control perspective	nadzorni vidik	<i>(ITIL Service Strategy)</i> An approach to the management of IT services, processes, functions, assets etc. There can be several different control perspectives on the same IT service, process etc., allowing different individuals or teams to focus on what is important and relevant to their specific role. Examples of control perspective include reactive and proactive management within IT operations, or a lifecycle view for an application project team.
131	control processes	nadzorni procesi	The ISO/IEC 20000 process group that includes change management and configuration management.
132	core service	osnovna storitev	<i>(ITIL Service Strategy)</i> A service that delivers the basic outcomes desired by one or more customers. A core service provides a specific level of utility and warranty. Customers may be offered a choice of utility and warranty through one or more service options. See also enabling service; enhancing service; IT service; service package.
133	cost	strošek	The amount of money spent on a specific activity, IT service or business unit. Costs consist of real cost (money), notional cost (such as people's time) and depreciation.
134	cost benefit analysis	analiza stroškov in koristi	An activity that analyses and compares the costs and the benefits involved in one or more alternative courses of action. See also business case; internal rate of return; net present value; return on investment; value on investment.
135	cost centre	stroškovno mesto	<i>(ITIL Service Strategy)</i> A business unit or project to which costs are assigned. A cost centre does not charge for services provided. An IT service provider can be run as a cost centre or a profit centre.
136	cost element	stroškovni element	<i>(ITIL Service Strategy)</i> The middle level of category to which costs are assigned in budgeting and accounting. The highest-level category is cost type. For example, a cost type of 'people' could have cost elements of payroll, staff benefits, expenses, training, overtime etc. Cost elements can be further broken down to give cost units. For example, the cost element 'expenses' could include cost units of hotels, transport, meals etc.
137	cost management	upravljanje stroškov	<i>(ITIL Service Strategy)</i> A general term that is used to refer to budgeting and accounting, and is sometimes used as a synonym for financial management.
138	cost model	stroškovni model	<i>(ITIL Service Strategy)</i> A framework used in budgeting and accounting in which all known costs can be recorded, categorized and allocated to specific customers, business units or projects. See also cost type; cost element; cost unit.
139	cost type	vrsta stroška	<i>(ITIL Service Strategy)</i> The highest level of category to which costs are assigned in budgeting and accounting – for example, hardware, software, people, accommodation, external and transfer. See also cost element; cost unit.
140	cost unit	stroškovna enota	<i>(ITIL Service Strategy)</i> The lowest level of category to which costs are assigned, cost units are usually things that can be easily counted (e.g. staff numbers, software licences) or things easily measured (e.g. CPU usage, electricity consumed). Cost units are included within cost elements. For example, a cost element of 'expenses' could include cost units of hotels, transport, meals etc. See also cost type.

#	Angleški pojem	Slovenski pojem	Angleški opis
141	cost effectiveness	stroškovna uspešnost	A measure of the balance between the effectiveness and cost of a service, process or activity. A cost-effective process is one that achieves its objectives at minimum cost. <i>See also</i> key performance indicator; return on investment; value for money.
142	countermeasure	protiukrep	Can be used to refer to any type of control. The term is most often used when referring to measures that increase resilience, fault tolerance or reliability of an IT service.
143	course corrections	popravki smeri	Changes made to a plan or activity that has already started to ensure that it will meet its objectives. Course corrections are made as a result of monitoring progress.
144	crisis management	krizno upravljanje	Crisis management is the process responsible for managing the wider implications of business continuity. A crisis management team is responsible for strategic issues such as managing media relations and shareholder confidence, and decides when to invoke business continuity plans.
145	critical success factor (CSF)	kritični dejavniki uspeha	Something that must happen if an IT service, process, plan, project or other activity is to succeed. Key performance indicators are used to measure the achievement of each critical success factor. For example, a critical success factor of 'protect IT services when making changes' could be measured by key performance indicators such as 'percentage reduction of unsuccessful changes', 'percentage reduction in changes causing incidents' etc.
146	CSI register	register izboljšav storitev	<i>(ITIL Continual Service Improvement)</i> A database or structured document used to record and manage improvement opportunities throughout their lifecycle.
147	culture	kultura	A set of values that is shared by a group of people, including expectations about how people should behave, their ideas, beliefs and practices. <i>See also</i> vision.
148	customer	stranka	Someone who buys goods or services. The customer of an IT service provider is the person or group who defines and agrees the service level targets. The term is also sometimes used informally to mean user – for example, 'This is a customer-focused organization.'
149	customer asset	sredstvo stranke	Any resource or capability of a customer. <i>See also</i> asset .
150	customer agreement portfolio	portfelj pogodb	<i>(ITIL Service Strategy)</i> A database or structured document used to manage service contracts or agreements between an IT service provider and its customers. Each IT service delivered to a customer should have a contract or other agreement that is listed in the customer agreement portfolio. <i>See also</i> customer-facing service; service catalogue; service portfolio.
151	customer portfolio	portfelj stranke	<i>(ITIL Service Strategy)</i> A database or structured document used to record all customers of the IT service provider. The customer portfolio is the business relationship manager's view of the customers who receive services from the IT service provider. <i>See also</i> customer agreement portfolio; service catalogue; service portfolio.
152	customer-facing service	storitev za stranko	<i>(ITIL Service Design)</i> An IT service that is visible to the customer. These are normally services that support the customer's business processes and facilitate one or more outcomes desired by the customer. All live customer-facing services, including those available for deployment, are recorded in the service catalogue along with customer-visible information about deliverables, prices, contact points, ordering and request processes. Other information such as relationships to supporting services and other CIs will also be recorded for internal use by the IT service provider.
153	dashboard	pregledna plošča	<i>(ITIL Service Operation)</i> A graphical representation of overall IT service performance and availability. Dashboard images may be updated in real time, and can also be included in management reports and web pages. Dashboards can be used to support service level management, event management and incident diagnosis.
154	Data-to-Information-to-Knowledge-to-Wisdom (DIKW)	Podatki-Informacije-Znanje-Modrost	<i>(ITIL Service Transition)</i> A way of understanding the relationships between data, information, knowledge and wisdom. DIKW shows how each of these builds on the others.

#	Angleški pojem	Slovenski pojem	Angleški opis
155	definitive media library (DML)	knjižnica potrjenih medijev (nosilcev)	(<i>ITIL Service Transition</i>) One or more locations in which the definitive and authorized versions of all software configuration items are securely stored. The definitive media library may also contain associated configuration items such as licences and documentation. It is a single logical storage area even if there are multiple locations. The definitive media library is controlled by service asset and configuration management and is recorded in the configuration management system.
156	deliverable	izdelek	Something that must be provided to meet a commitment in a service level agreement or a contract. It is also used in a more informal way to mean a planned output of any process.
157	demand management	upravljanje zahtev	(<i>ITIL Service Design</i>) (<i>ITIL Service Strategy</i>) The process responsible for understanding, anticipating and influencing customer demand for services. Demand management works with capacity management to ensure that the service provider has sufficient capacity to meet the required demand. At a strategic level, demand management can involve analysis of patterns of business activity and user profiles, while at a tactical level, it can involve the use of differential charging to encourage customers to use IT services at less busy times, or require short-term activities to respond to unexpected demand or the failure of a configuration item.
158	Deming Cycle	Demingov krog	See Plan-Do-Check-Act.
159	dependency	odvisnost	The direct or indirect reliance of one process or activity on another.
160	deployment	postavitev	(<i>ITIL Service Transition</i>) The activity responsible for movement of new or changed hardware, software, documentation, process etc. to the live environment. Deployment is part of the release and deployment management process.
161	depreciation	amortizacija	(<i>ITIL Service Strategy</i>) A measure of the reduction in value of an asset over its life. This is based on wearing out, consumption or other reduction in the useful economic value.
162	design	oblikovanje	(<i>ITIL Service Design</i>) An activity or process that identifies requirements and then defines a solution that is able to meet these requirements. <i>See also</i> service design.
163	design coordination	koordinacija oblikovanja	(<i>ITIL Service Design</i>) The process responsible for coordinating all service design activities, processes and resources. Design coordination ensures the consistent and effective design of new or changed IT services, service management information systems, architectures, technology, processes, information and metrics.
164	detection	zaznava	(<i>ITIL Service Operation</i>) A stage in the expanded incident lifecycle. Detection results in the incident becoming known to the service provider. Detection can be automatic or the result of a user logging an incident.
165	development	razvoj	(<i>ITIL Service Design</i>) The process responsible for creating or modifying an IT service or application ready for subsequent release and deployment. Development is also used to mean the role or function that carries out development work. This process is not described in detail within the core ITIL publications.
166	development environment	razvojno okolje	(<i>ITIL Service Design</i>) An environment used to create or modify IT services or applications. Development environments are not typically subjected to the same degree of control as test or live environments. <i>See also</i> development.
167	diagnosis	diagnoza	(<i>ITIL Service Operation</i>) A stage in the incident and problem lifecycles. The purpose of diagnosis is to identify a workaround for an incident or the root cause of a problem.
168	diagnostic script	diagnotični opomnik	(<i>ITIL Service Operation</i>) A structured set of questions used by service desk staff to ensure they ask the correct questions, and to help them classify, resolve and assign incidents. Diagnostic scripts may also be made available to users to help them diagnose and resolve their own incidents.

#	Angleški pojem	Slovenski pojem	Angleški opis
169	differential charging	časovno prilagojeno zaračunavanje	A technique used to support demand management by charging different amounts for the same function of an IT service under different circumstances. For example, reduced charges outside peak times, or increased charges for users who exceed a bandwidth allocation.
170	direct cost	neposredni strošek	<i>(ITIL Service Strategy)</i> The cost of providing an IT service which can be allocated in full to a specific customer, cost centre, project etc. For example, the cost of providing non-shared servers or software licences. <i>See also</i> indirect cost.
171	directory service	imeniška storitev	<i>(ITIL Service Operation)</i> An application that manages information about IT infrastructure available on a network, and corresponding user access rights.
172	document	dokument	Information in readable form. A document may be paper or electronic – for example, a policy statement, service level agreement, incident record or diagram of a computer room layout. <i>See also</i> record.
173	downtime	čas izpada	<i>(ITIL Service Design)</i> <i>(ITIL Service Operation)</i> The time when an IT service or other configuration item is not available during its agreed service time. The availability of an IT service is often calculated from agreed service time and downtime.
174	driver	gonilnik	Something that influences strategy, objectives or requirements – for example, new legislation or the actions of competitors.
175	early life support (ELS)	podpora ob uvajanju	<i>(ITIL Service Transition)</i> A stage in the service lifecycle that occurs at the end of deployment and before the service is fully accepted into operation. During early life support, the service provider reviews key performance indicators, service levels and monitoring thresholds and may implement improvements to ensure that service targets can be met. The service provider may also provide additional resources for incident and problem management during this time.
176	economies of scale	ekonomija obsega	<i>(ITIL Service Strategy)</i> The reduction in average cost that is possible from increasing the usage of an IT service or asset. <i>See also</i> economies of scope.
177	economies of scope	ekonomija dodatne uporabe	<i>(ITIL Service Strategy)</i> The reduction in cost that is allocated to an IT service by using an existing asset for an additional purpose. For example, delivering a new IT service from an existing IT infrastructure. <i>See also</i> economies of scale.
178	effectiveness	uspešnost	<i>(ITIL Continual Service Improvement)</i> A measure of whether the objectives of a process, service or activity have been achieved. An effective process or activity is one that achieves its agreed objectives. <i>See also</i> key performance indicator.
179	efficiency	učinkovitost	<i>(ITIL Continual Service Improvement)</i> A measure of whether the right amount of resource has been used to deliver a process, service or activity. An efficient process achieves its objectives with the minimum amount of time, money, people or other resources. <i>See also</i> key performance indicator.
180	emergency change	nujna sprememba	<i>(ITIL Service Transition)</i> A change that must be introduced as soon as possible – for example, to resolve a major incident or implement a security patch. The change management process will normally have a specific procedure for handling emergency changes. <i>See also</i> emergency change advisory board.
181	emergency change advisory board (ECAB)	odbor za nujne spremembe (ONS)	<i>(ITIL Service Transition)</i> A subgroup of the change advisory board that makes decisions about emergency changes. Membership may be decided at the time a meeting is called, and depends on the nature of the emergency change.
182	enabling service	tvorno storitev	<i>(ITIL Service Strategy)</i> A service that is needed in order to deliver a core service. Enabling services may or may not be visible to the customer, but they are not offered to customers in their own right. <i>See also</i> enhancing service.

#	Angleški pojem	Slovenski pojem	Angleški opis
183	enhancing service	krepljena storitev	<i>(ITIL Service Strategy)</i> A service that is added to a core service to make it more attractive to the customer. Enhancing services are not essential to the delivery of a core service but are used to encourage customers to use the core services or to differentiate the service provider from its competitors. <i>See also</i> enabling service; excitement factor.
184	enterprise financial management	upravljanje financ v podjetju	<i>(ITIL Service Strategy)</i> The function and processes responsible for managing the overall organization's budgeting, accounting and charging requirements. Enterprise financial management is sometimes referred to as the 'corporate' financial department. <i>See also</i> financial management for IT services.
185	environment	okolje	<i>(ITIL Service Transition)</i> A subset of the IT infrastructure that is used for a particular purpose – for example, live environment, test environment, build environment. Also used in the term 'physical environment' to mean the accommodation, air conditioning, power system etc. Environment is used as a generic term to mean the external conditions that influence or affect something.
186	error	napaka	<i>(ITIL Service Operation)</i> A design flaw or malfunction that causes a failure of one or more IT services or other configuration items. A mistake made by a person or a faulty process that impacts a configuration item is also an error.
187	escalation	eskalacija	<i>(ITIL Service Operation)</i> An activity that obtains additional resources when these are needed to meet service level targets or customer expectations. Escalation may be needed within any IT service management process, but is most commonly associated with incident management, problem management and the management of customer complaints. There are two types of escalation: functional escalation and hierarchic escalation.
188	eSourcing Capability Model for Client Organizations (eSCM-CL)	zmožnostni model informacijskih storitev za stranke (eSCM-CL)	<i>(ITIL Service Strategy)</i> A framework to help organizations in their analysis and decision-making on service sourcing models and strategies. It was developed by Carnegie Mellon University in the US. <i>See also</i> eSourcing Capability Model for Service Providers.
189	eSourcing Capability Model for Service Providers (eSCM-SP)	zmožnostni model informacijskih storitev za ponudnike storitev (eSCM-CL)	<i>(ITIL Service Strategy)</i> A framework to help IT service providers develop their IT service management capabilities from a service sourcing perspective. It was developed by Carnegie Mellon University in the US. <i>See also</i> eSourcing Capability Model for Client Organizations.
190	estimation	ocenjevanje	The use of experience to provide an approximate value for a metric or cost. Estimation is also used in capacity and availability management as the cheapest and least accurate modelling method.
191	event	dogodek	<i>(ITIL Service Operation)</i> A change of state that has significance for the management of an IT service or other configuration item. The term is also used to mean an alert or notification created by any IT service, configuration item or monitoring tool. Events typically require IT operations personnel to take actions, and often lead to incidents being logged.
192	event management	upravljanje dogodkov	<i>(ITIL Service Operation)</i> The process responsible for managing events throughout their lifecycle. Event management is one of the main activities of IT operations.
193	exception report	poročilo o odstopanjih	A document containing details of one or more key performance indicators or other important targets that have exceeded defined thresholds. Examples include service level agreement targets being missed or about to be missed, and a performance metric indicating a potential capacity problem.
194	excitement attribute	dejavnik navdušenja	<i>See</i> excitement factor.
195	excitement factor	dejavnik navdušenja	<i>(ITIL Service Strategy)</i> An attribute added to something to make it more attractive or more exciting to the customer. For example, a restaurant may provide a free drink with every meal. <i>See also</i> enhancing service.

#	Angleški pojem	Slovenski pojem	Angleški opis
196	expanded incident lifecycle	podroben življenjski krog dogodka	<i>(ITIL Continual Service Improvement) (ITIL Service Design)</i> Detailed stages in the lifecycle of an incident. The stages are detection, diagnosis, repair, recovery and restoration. The expanded incident lifecycle is used to help understand all contributions to the impact of incidents and to plan for how these could be controlled or reduced.
197	external customer	zunanji naročnik	A customer who works for a different business from the IT service provider. <i>See also</i> external service provider; internal customer.
198	external metric	zunanja metrika	A metric that is used to measure the delivery of IT service to a customer. External metrics are usually defined in service level agreements and reported to customers. <i>See also</i> internal metric.
199	external service provider	zunanji ponudnik storitev	<i>(ITIL Service Strategy)</i> An IT service provider that is part of a different organization from its customer. An IT service provider may have both internal and external customers. <i>See also</i> outsourcing; Type III service provider.
200	facilities management	upravljanje objektov	<i>(ITIL Service Operation)</i> The function responsible for managing the physical environment where the IT infrastructure is located. Facilities management includes all aspects of managing the physical environment – for example, power and cooling, building access management, and environmental monitoring.
201	failure	odpoved	<i>(ITIL Service Operation)</i> Loss of ability to operate to specification, or to deliver the required output. The term may be used when referring to IT services, processes, activities, configuration items etc. A failure often causes an incident.
202	fast recovery	hitro okrevanje	<i>(ITIL Service Design)</i> A recovery option that is also known as hot standby. Fast recovery normally uses a dedicated fixed facility with computer systems and software configured ready to run the IT services. Fast recovery typically takes up to 24 hours but may be quicker if there is no need to restore data from backups.
203	fault	napaka	<i>See</i> error.
204	fault tolerance	odpornost na napake	<i>(ITIL Service Design)</i> The ability of an IT service or other configuration item to continue to operate correctly after failure of a component part. <i>See also</i> countermeasure; resilience.
205	fault tree analysis (FTA)	analiza drevesne napake	<i>(ITIL Continual Service Improvement) (ITIL Service Design)</i> A technique that can be used to determine a chain of events that has caused an incident, or may cause an incident in the future. Fault tree analysis represents a chain of events using Boolean notation in a diagram.
206	financial management	finančno upravljanje informacijskih storitev	<i>(ITIL Service Strategy)</i> A generic term used to describe the function and processes responsible for managing an organization's budgeting, accounting and charging requirements. Enterprise financial management is the specific term used to describe the function and processes from the perspective of the overall organization. Financial management for IT services is the specific term used to describe the function and processes from the perspective of the IT service provider.
207	financial management for IT services	upravljanje financ za storitve IT	<i>(ITIL Service Strategy)</i> The function and processes responsible for managing an IT service provider's budgeting, accounting and charging requirements. Financial management for IT services secures an appropriate level of funding to design, develop and deliver services that meet the strategy of the organization in a cost-effective manner. <i>See also</i> enterprise financial management.
208	financial year	poslovno leto	<i>(ITIL Service Strategy)</i> An accounting period covering 12 consecutive months. A financial year may start on any date (for example, 1 April to 31 March).
209	first-line support	prva raven podpore	<i>(ITIL Service Operation)</i> The first level in a hierarchy of support groups involved in the resolution of incidents. Each level contains more specialist skills, or has more time or other resources. <i>See also</i> escalation.
210	fishbone diagram	diagram ribje kosti	<i>See</i> Ishikawa diagram.

#	Angleški pojem	Slovenski pojem	Angleški opis
211	fit for purpose	ustrezno namenu	(<i>ITIL Service Strategy</i>) The ability to meet an agreed level of utility. Fit for purpose is also used informally to describe a process, configuration item, IT service etc. that is capable of meeting its objectives or service levels. Being fit for purpose requires suitable design, implementation, control and maintenance.
212	fit for use	primeren za uporabo	(<i>ITIL Service Strategy</i>) The ability to meet an agreed level of warranty. Being fit for use requires suitable design, implementation, control and maintenance.
213	fixed asset	osnovno sredstvo	(<i>ITIL Service Transition</i>) A tangible business asset that has a long-term useful life (for example, a building, a piece of land, a server or a software licence). <i>See also</i> service asset; configuration item.
214	fixed asset management	upravljanje osnovnih sredstev	(<i>ITIL Service Transition</i>) The process responsible for tracking and reporting the value and ownership of fixed assets throughout their lifecycle. Fixed asset management maintains the asset register and is usually carried out by the overall business, rather than by the IT organization. Fixed asset management is sometimes called financial asset management and is not described in detail within the core ITIL publications.
215	fixed cost	stalni stroški	(<i>ITIL Service Strategy</i>) A cost that does not vary with IT service usage – for example, the cost of server hardware. <i>See also</i> variable cost.
216	fixed facility	stalen objekt	(<i>ITIL Service Design</i>) A permanent building, available for use when needed by an IT service continuity plan. <i>See also</i> portable facility; recovery option.
217	follow the sun	tam, kjer je dan	(<i>ITIL Service Operation</i>) A methodology for using service desks and support groups around the world to provide seamless 24/7 service. Calls, incidents, problems and service requests are passed between groups in different time zones.
218	fulfilment	izpolnitev	Performing activities to meet a need or requirement – for example, by providing a new IT service, or meeting a service request.
219	function	funkcija	A team or group of people and the tools or other resources they use to carry out one or more processes or activities – for example, the service desk. The term also has two other meanings: I An intended purpose of a configuration item, person, team, process or IT service. For example, one function of an email service may be to store and forward outgoing mails, while the function of a business process may be to despatch goods to customers.I To perform the intended purpose correctly, as in ‘The computer is functioning.’
220	functional escalation	funkcionalna eskalacija	(<i>ITIL Service Operation</i>) Transferring an incident, problem or change to a technical team with a higher level of expertise to assist in an escalation.
221	gap analysis	analiza vrzeli	(<i>ITIL Continual Service Improvement</i>) An activity that compares two sets of data and identifies the differences. Gap analysis is commonly used to compare a set of requirements with actual delivery. <i>See also</i> benchmarking.
222	governance	upravljanje; vodenje	Ensures that policies and strategy are actually implemented, and that required processes are correctly followed. Governance includes defining roles and responsibilities, measuring and reporting, and taking actions to resolve any issues identified.
223	gradual recovery	počasna obnovitev	(<i>ITIL Service Design</i>) A recovery option that is also known as cold standby. Gradual recovery typically uses a portable or fixed facility that has environmental support and network cabling, but no computer systems. The hardware and software are installed as part of the IT service continuity plan. Gradual recovery typically takes more than three days, and may take significantly longer.
224	guideline	smernice	A document describing best practice, which recommends what should be done. Compliance with a guideline is not normally enforced. <i>See also</i> standard.
225	hierarchic escalation	hierarhična eskalacija	(<i>ITIL Service Operation</i>) Informing or involving more senior levels of management to assist in an escalation.

#	Angleški pojem	Slovenski pojem	Angleški opis
226	high availability	visoka razpoložljivost	<i>(ITIL Service Design)</i> An approach or design that minimizes or hides the effects of configuration item failure from the users of an IT service. High availability solutions are designed to achieve an agreed level of availability and make use of techniques such as fault tolerance, resilience and fast recovery to reduce the number and impact of incidents.
227	hot standby	vroča pripravljenost	<i>See</i> fast recovery; immediate recovery.
228	identity	identiteta	<i>(ITIL Service Operation)</i> A unique name that is used to identify a user, person or role. The identity is used to grant rights to that user, person or role. Example identities might be the username SmithJ or the role 'change manager'.
229	immediate recovery	takojšnja obnovitev	<i>(ITIL Service Design)</i> A recovery option that is also known as hot standby. Provision is made to recover the IT service with no significant loss of service to the customer. Immediate recovery typically uses mirroring, load balancing and split-site technologies.
230	impact	učinek; vpliv	<i>(ITIL Service Operation)</i> <i>(ITIL Service Transition)</i> A measure of the effect of an incident, problem or change on business processes. Impact is often based on how service levels will be affected. Impact and urgency are used to assign priority.
231	incident	incident	<i>(ITIL Service Operation)</i> An unplanned interruption to an IT service or reduction in the quality of an IT service. Failure of a configuration item that has not yet affected service is also an incident – for example, failure of one disk from a mirror set.
232	incident management	upravljanje incidentov	<i>(ITIL Service Operation)</i> The process responsible for managing the lifecycle of all incidents. Incident management ensures that normal service operation is restored as quickly as possible and the business impact is minimized.
233	incident record	zapis o incidentu	<i>(ITIL Service Operation)</i> A record containing the details of an incident. Each incident record documents the lifecycle of a single incident.
234	indirect cost	posredni stroški	<i>(ITIL Service Strategy)</i> The cost of providing an IT service which cannot be allocated in full to a specific customer – for example, the cost of providing shared servers or software licences. Also known as overhead. <i>See also</i> direct cost.
235	information security management (ISM)	upravljanje informacijske varnosti	<i>(ITIL Service Design)</i> The process responsible for ensuring that the confidentiality, integrity and availability of an organization's assets, information, data and IT services match the agreed needs of the business. Information security management supports business security and has a wider scope than that of the IT service provider, and includes handling of paper, building access, phone calls etc. for the entire organization. <i>See also</i> security management information system.
236	information security management system (ISMS)	sistem za upravljanje informacijske varnosti	<i>(ITIL Service Design)</i> The framework of policy, processes, functions, standards, guidelines and tools that ensures an organization can achieve its information security management objectives. <i>See also</i> security management information system.
237	information security policy	politika informacijske varnosti	<i>(ITIL Service Design)</i> The policy that governs the organization's approach to information security management.
238	information system	informacijski sistem	<i>See</i> management information system.
239	information technology (IT)	informacijska tehnologija	The use of technology for the storage, communication or processing of information. The technology typically includes computers, telecommunications, applications and other software. The information may include business data, voice, images, video etc. Information technology is often used to support business processes through IT services.
240	infrastructure service	infrastrukturna storitev	A type of supporting service that provides hardware, network or other data centre components. The term is also used as a synonym for supporting service.

#	Angleški pojem	Slovenski pojem	Angleški opis
241	insourcing	notranje izvajanje	<i>(ITIL Service Strategy)</i> Using an internal service provider to manage IT services. The term insourcing is also used to describe the act of transferring the provision of an IT service from an external service provider to an internal service provider. <i>See also</i> service sourcing.
242	integrity	celovitost	<i>(ITIL Service Design)</i> A security principle that ensures data and configuration items are modified only by authorized personnel and activities. Integrity considers all possible causes of modification, including software and hardware failure, environmental events, and human intervention.
243	interactive voice response (IVR)	interaktivni govorni odzivnik	<i>(ITIL Service Operation)</i> A form of automatic call distribution that accepts user input, such as key presses and spoken commands, to identify the correct destination for incoming calls.
244	intermediate recovery	zmerno hitro okrevanje	<i>(ITIL Service Design)</i> A recovery option that is also known as warm standby. Intermediate recovery usually uses a shared portable or fixed facility that has computer systems and network components. The hardware and software will need to be configured, and data will need to be restored, as part of the IT service continuity plan. Typical recovery times for intermediate recovery are one to three days.
245	internal customer	notranja stranka	A customer who works for the same business as the IT service provider. <i>See also</i> external customer; internal service provider.
246	internal metric	notranja metrika	A metric that is used within the IT service provider to monitor the efficiency, effectiveness or cost effectiveness of the IT service provider's internal processes. Internal metrics are not normally reported to the customer of the IT service. <i>See also</i> external metric.
247	internal rate of return (IRR)	notranja stopnja donosa	<i>(ITIL Service Strategy)</i> A technique used to help make decisions about capital expenditure. It calculates a figure that allows two or more alternative investments to be compared. A larger internal rate of return indicates a better investment. <i>See also</i> net present value; return on investment.
248	internal service provider	notranji ponudnik storitev	<i>(ITIL Service Strategy)</i> An IT service provider that is part of the same organization as its customer. An IT service provider may have both internal and external customers. <i>See also</i> insourcing; Type I service provider; Type II service provider.
249	International Organization for Standardization (ISO)	mednarodna organizacija za standardizacijo	The International Organization for Standardization (ISO) is the world's largest developer of standards. ISO is a non-governmental organization that is a network of the national standards institutes of 156 countries. <i>See</i> www.iso.org for further information about ISO.
250	International Standards Organization	mednarodna organizacija za standardizacijo	<i>See</i> International Organization for Standardization.
251	internet service provider (ISP)	ponudnik spletnih storitev	An external service provider that provides access to the internet. Most ISPs also provide other IT services such as web hosting.
252	invocation	sprožitev	<i>(ITIL Service Design)</i> Initiation of the steps defined in a plan – for example, initiating the IT service continuity plan for one or more IT services.
253	Ishikawa diagram	diagram Ishikawa	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Operation)</i> A technique that helps a team to identify all the possible causes of a problem. Originally devised by Kaoru Ishikawa, the output of this technique is a diagram that looks like a fishbone.
254	ISO 9000	ISO 9000	A generic term that refers to a number of international standards and guidelines for quality management systems. <i>See</i> www.iso.org for more information. <i>See also</i> International Organization for Standardization.
255	ISO 9001	ISO 9001	An international standard for quality management systems. <i>See also</i> ISO 9000; standard.
256	ISO/IEC 20000	ISO/IEC 20000	An international standard for IT service management.
257	ISO/IEC 27001	ISO/IEC 27001	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> An international specification for information security management. The corresponding code of practice is ISO/IEC 27002. <i>See also</i> standard.
258	ISO/IEC 27002	ISO/IEC 27002	<i>(ITIL Continual Service Improvement)</i> An international code of practice for information security management. The corresponding specification is ISO/IEC 27001. <i>See also</i> standard.

#	Angleški pojem	Slovenski pojem	Angleški opis
259	IT accounting	računovodstvo IT	See accounting.
260	IT infrastructure	infrastruktura IT	All of the hardware, software, networks, facilities etc. that are required to develop, test, deliver, monitor, control or support applications and IT services. The term includes all of the information technology but not the associated people, processes and documentation.
261	IT operations	obratovanje IT	(<i>ITIL Service Operation</i>) Activities carried out by IT operations control, including console management/operations bridge, job scheduling, backup and restore, and print and output management. IT operations is also used as a synonym for service operation.
262	IT operations control	nadzor obratovanja IT	(<i>ITIL Service Operation</i>) The function responsible for monitoring and control of the IT services and IT infrastructure. See also operations bridge.
263	IT operations management	upravljanje obratovanja IT	(<i>ITIL Service Operation</i>) The function within an IT service provider that performs the daily activities needed to manage IT services and the supporting IT infrastructure. IT operations management includes IT operations control and facilities management.
264	IT service	storitev IT	A service provided by an IT service provider. An IT service is made up of a combination of information technology, people and processes. A customer-facing IT service directly supports the business processes of one or more customers and its service level targets should be defined in a service level agreement. Other IT services, called supporting services, are not directly used by the business but are required by the service provider to deliver customer-facing services. See also core service; enabling service; enhancing service; service; service package.
265	IT service continuity management (ITSCM)	zagotavljanje neprekinjenosti storitev IT	(<i>ITIL Service Design</i>) The process responsible for managing risks that could seriously affect IT services. IT service continuity management ensures that the IT service provider can always provide minimum agreed service levels, by reducing the risk to an acceptable level and planning for the recovery of IT services. IT service continuity management supports business continuity management.
266	IT service continuity plan	načrt za neprekinjenost storitev IT	(<i>ITIL Service Design</i>) A plan defining the steps required to recover one or more IT services. The plan also identifies the triggers for invocation, people to be involved, communications etc. The IT service continuity plan should be part of a business continuity plan.
267	IT service management (ITSM)	upravljanje storitev IT	The implementation and management of quality IT services that meet the needs of the business. IT service management is performed by IT service providers through an appropriate mix of people, process and information technology. See also service management.
268	IT Service Management Forum (itSMF)	forum za upravljanje storitev IT	The IT Service Management Forum is an independent organization dedicated to promoting a professional approach to IT service management. The itSMF is a not-for-profit membership organization with representation in many countries around the world (itSMF chapters). The itSMF and its membership contribute to the development of ITIL and associated IT service management standards. See www.itsmf.com for more information.
269	IT service provider	ponudnik storitev IT	(<i>ITIL Service Strategy</i>) A service provider that provides IT services to internal or external customers.
270	IT steering group (ISG)	usmerjevalna skupina IT	(<i>ITIL Service Design</i>) (<i>ITIL Service Strategy</i>) A formal group that is responsible for ensuring that business and IT service provider strategies and plans are closely aligned. An IT steering group includes senior representatives from the business and the IT service provider. Also known as IT strategy group or IT steering committee.

#	Angleški pojem	Slovenski pojem	Angleški opis
271	ITIL®	ITIL®	A set of best-practice publications for IT service management. Owned by the Cabinet Office (part of HM Government), ITIL gives guidance on the provision of quality IT services and the processes, functions and other capabilities needed to support them. The ITIL framework is based on a service lifecycle and consists of five lifecycle stages (service strategy, service design, service transition, service operation and continual service improvement), each of which has its own supporting publication. There is also a set of complementary ITIL publications providing guidance specific to industry sectors, organization types, operating models and technology architectures. See www.itil-officialsite.com for more information.
272	job description	opis del in nalog	A document that defines the roles, responsibilities, skills and knowledge required by a particular person. One job description can include multiple roles – for example, the roles of configuration manager and change manager may be carried out by one person.
273	job scheduling	urnik obdelav	<i>(ITIL Service Operation)</i> Planning and managing the execution of software tasks that are required as part of an IT service. Job scheduling is carried out by IT operations management, and is often automated using software tools that run batch or online tasks at specific times of the day, week, month or year.
274	Kano model	Kanov model	<i>(ITIL Service Strategy)</i> A model developed by Noriaki Kano that is used to help understand customer preferences. The Kano model considers attributes of an IT service grouped into areas such as basic factors, excitement factors, performance factors etc.
275	Kepner and Tregoe analysis	analiza Kepner & Tregoe	<i>(ITIL Service Operation)</i> A structured approach to problem solving. The problem is analysed in terms of what, where, when and extent. Possible causes are identified, the most probable cause is tested, and the true cause is verified.
276	key performance indicator (KPI)	ključni kazalnik delovanja	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> A metric that is used to help manage an IT service, process, plan, project or other activity. Key performance indicators are used to measure the achievement of critical success factors. Many metrics may be measured, but only the most important of these are defined as key performance indicators and used to actively manage and report on the process, IT service or activity. They should be selected to ensure that efficiency, effectiveness and cost effectiveness are all managed.
277	knowledge base	zbirka znanja	<i>(ITIL Service Transition)</i> A logical database containing data and information used by the service knowledge management system.
278	knowledge management	upravljanje znanja	<i>(ITIL Service Transition)</i> The process responsible for sharing perspectives, ideas, experience and information, and for ensuring that these are available in the right place and at the right time. The knowledge management process enables informed decisions, and improves efficiency by reducing the need to rediscover knowledge. <i>See also</i> Data-to-Information-to-Knowledge-to-Wisdom; service knowledge management system.
279	known error	znana napaka	<i>(ITIL Service Operation)</i> A problem that has a documented root cause and a workaround. Known errors are created and managed throughout their lifecycle by problem management. Known errors may also be identified by development or suppliers.
280	known error database (KEDB)	podatkovna zbirka znanih napak	<i>(ITIL Service Operation)</i> A database containing all known error records. This database is created by problem management and used by incident and problem management. The known error database may be part of the configuration management system, or may be stored elsewhere in the service knowledge management system.
281	known error record	zapis o znani napaki	<i>(ITIL Service Operation)</i> A record containing the details of a known error. Each known error record documents the lifecycle of a known error, including the status, root cause and workaround. In some implementations, a known error is documented using additional fields in a problem record.

#	Angleški pojem	Slovenski pojem	Angleški opis
282	lifecycle	življenjski krog	The various stages in the life of an IT service, configuration item, incident, problem, change etc. The lifecycle defines the categories for status and the status transitions that are permitted. For example: I The lifecycle of an application includes requirements, design, build, deploy, operate, optimize I The expanded incident lifecycle includes detection, diagnosis, repair, recovery and restoration I The lifecycle of a server may include: ordered, received, in test, live, disposed etc.
283	line of service (LOS)	vrsta storitve	<i>(ITIL Service Strategy)</i> A core service or service package that has multiple service options. A line of service is managed by a service owner and each service option is designed to support a particular market segment.
284	live	živ	<i>(ITIL Service Transition)</i> Refers to an IT service or other configuration item that is being used to deliver service to a customer.
285	live environment	produksijsko okolje	<i>(ITIL Service Transition)</i> A controlled environment containing live configuration items used to deliver IT services to customers.
286	maintainability	vzdrževalnost	<i>(ITIL Service Design)</i> A measure of how quickly and effectively an IT service or other configuration item can be restored to normal working after a failure. Maintainability is often measured and reported as MTRS. Maintainability is also used in the context of software or IT service development to mean ability to be changed or repaired easily.
287	major incident	večji incident	<i>(ITIL Service Operation)</i> The highest category of impact for an incident. A major incident results in significant disruption to the business.
288	manageability	upravljivost	An informal measure of how easily and effectively an IT service or other component can be managed.
289	management information	informacije za vodstvo	Information that is used to support decision making by managers. Management information is often generated automatically by tools supporting the various IT service management processes. Management information often includes the values of key performance indicators, such as 'percentage of changes leading to incidents' or 'first-time fix rate'.
290	management information system (MIS)	upravljavski informacijski sistem	<i>(ITIL Service Design)</i> A set of tools, data and information that is used to support a process or function. Examples include the availability management information system and the supplier and contract management information system. <i>See also</i> service knowledge management system.
291	Management of Risk (M_o_R®)	upravljanje tveganj (M_o_R®)	M_o_R includes all the activities required to identify and control the exposure to risk, which may have an impact on the achievement of an organization's business objectives. <i>See</i> www.mor-officialsite.com for more details.
292	management system	upravljavski sistem	The framework of policy, processes, functions, standards, guidelines and tools that ensures an organization or part of an organization can achieve its objectives. This term is also used with a smaller scope to support a specific process or activity – for example, an event management system or risk management system. <i>See also</i> system.
293	manual workaround	ročna nadomestna rešitev	<i>(ITIL Continual Service Improvement)</i> A workaround that requires manual intervention. Manual workaround is also used as the name of a recovery option in which the business process operates without the use of IT services. This is a temporary measure and is usually combined with another recovery option.
294	marginal cost	mejni strošek	<i>(ITIL Service Strategy)</i> The increase or decrease in the cost of producing one more, or one less, unit of output – for example, the cost of supporting an additional user.
295	market space	tržišče	<i>(ITIL Service Strategy)</i> Opportunities that an IT service provider could exploit to meet the business needs of customers. Market spaces identify the possible IT services that an IT service provider may wish to consider delivering.

#	Angleški pojem	Slovenski pojem	Angleški opis
296	maturity	zrelost	<i>(ITIL Continual Service Improvement)</i> A measure of the reliability, efficiency and effectiveness of a process, function, organization etc. The most mature processes and functions are formally aligned to business objectives and strategy, and are supported by a framework for continual improvement.
297	maturity level	raven zrelosti	A named level in a maturity model, such as the Carnegie Mellon Capability Maturity Model Integration.
298	mean time between failures (MTBF)	povprečni čas med odpovedma	<i>(ITIL Service Design)</i> A metric for measuring and reporting reliability. MTBF is the average time that an IT service or other configuration item can perform its agreed function without interruption. This is measured from when the configuration item starts working, until it next fails.
299	mean time between service incidents (MTBSI)	povprečnim časom med izpadoma storitve	<i>(ITIL Service Design)</i> A metric used for measuring and reporting reliability. It is the mean time from when a system or IT service fails, until it next fails. MTBSI is equal to MTBF plus MTRS.
300	mean time to repair (MTTR)	povprečni čas popravila	The average time taken to repair an IT service or other configuration item after a failure. MTTR is measured from when the configuration item fails until it is repaired. MTTR does not include the time required to recover or restore. It is sometimes incorrectly used instead of mean time to restore service.
301	mean time to restore service (MTRS)	povprečni čas obnovitve storitve	The average time taken to restore an IT service or other configuration item after a failure. MTRS is measured from when the configuration item fails until it is fully restored and delivering its normal functionality. <i>See also</i> maintainability; mean time to repair.
302	metric	metrika	<i>(ITIL Continual Service Improvement)</i> Something that is measured and reported to help manage a process, IT service or activity. <i>See also</i> key performance indicator.
303	middleware	vmesna programska oprema	<i>(ITIL Service Design)</i> Software that connects two or more software components or applications. Middleware is usually purchased from a supplier, rather than developed within the IT service provider. <i>See also</i> commercial off the shelf.
304	mission	poslanstvo	A short but complete description of the overall purpose and intentions of an organization. It states what is to be achieved, but not how this should be done. <i>See also</i> vision.
305	model	model	A representation of a system, process, IT service, configuration item etc. that is used to help understand or predict future behaviour.
306	modelling	modeliranje	A technique that is used to predict the future behaviour of a system, process, IT service, configuration item etc. Modelling is commonly used in financial management, capacity management and availability management.
307	monitor control loop	spremljanje s povratno zanko	<i>(ITIL Service Operation)</i> Monitoring the output of a task, process, IT service or other configuration item; comparing this output to a predefined norm; and taking appropriate action based on this comparison.
308	monitoring	spremljanje	<i>(ITIL Service Operation)</i> Repeated observation of a configuration item, IT service or process to detect events and to ensure that the current status is known.
309	near-shore	izvajanje v bližji tujini	<i>(ITIL Service Strategy)</i> Provision of services from a country near the country where the customer is based. This can be the provision of an IT service, or of supporting functions such as a service desk. <i>See also</i> offshore; onshore.
310	net present value (NPV)	neto sedanja vrednost	<i>(ITIL Service Strategy)</i> A technique used to help make decisions about capital expenditure. It compares cash inflows with cash outflows. Positive net present value indicates that an investment is worthwhile. <i>See also</i> internal rate of return; return on investment.
311	normal change	navadna sprememba	<i>(ITIL Service Transition)</i> A change that is not an emergency change or a standard change. Normal changes follow the defined steps of the change management process.
312	normal service operation	redno obratovanje storitve	<i>(ITIL Service Operation)</i> An operational state where services and configuration items are performing within their agreed service and operational levels.

#	Angleški pojem	Slovenski pojem	Angleški opis
313	notional charging	informativno zaračunavanje	<i>(ITIL Service Strategy)</i> An approach to charging for IT services. Charges to customers are calculated and customers are informed of the charge, but no money is actually transferred. Notional charging is sometimes introduced to ensure that customers are aware of the costs they incur, or as a stage during the introduction of real charging.
314	objective	cilj	The outcomes required from a process, activity or organization in order to ensure that its purpose will be fulfilled. Objectives are usually expressed as measurable targets. The term is also informally used to mean a requirement.
315	off the shelf	gotov izdelek	See commercial off the shelf.
316	Office of Government Commerce (OGC)	britanski trgovinski urad (OCG)	OGC (former owner of Best Management Practice) and its functions have moved into the Cabinet Office as part of HM Government. See www.cabinetoffice.gov.uk
317	offshore	zunanje izvajanje v daljni tujini	<i>(ITIL Service Strategy)</i> Provision of services from a location outside the country where the customer is based, often in a different continent. This can be the provision of an IT service, or of supporting functions such as a service desk. See also near-shore; onshore.
318	onshore	zunanje izvajanje doma	<i>(ITIL Service Strategy)</i> Provision of services from a location within the country where the customer is based. See also near-shore; offshore.
319	operate	obratovati	To perform as expected. A process or configuration item is said to operate if it is delivering the required outputs. Operate also means to perform one or more operations. For example, to operate a computer is to do the day-to-day operations needed for it to perform as expected.
320	operation	izvajanje; obratovanje	<i>(ITIL Service Operation)</i> Day-to-day management of an IT service, system or other configuration item. Operation is also used to mean any predefined activity or transaction – for example, loading a magnetic tape, accepting money at a point of sale, or reading data from a disk drive.
321	operational	obratovalen	The lowest of three levels of planning and delivery (strategic, tactical, operational). Operational activities include the day-to-day or short-term planning or delivery of a business process or IT service management process. The term is also a synonym for live.
322	operational cost	obratovalni stroški	The cost resulting from running the IT services, which often involves repeating payments – for example, staff costs, hardware maintenance and electricity (also known as current expenditure or revenue expenditure). See also capital expenditure.
323	operational expenditure (OPEX)	obratovalni izdatki	See operational cost.
324	operational level agreement (OLA)	dogovor o ravni obratovanja	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> An agreement between an IT service provider and another part of the same organization. It supports the IT service provider's delivery of IT services to customers and defines the goods or services to be provided and the responsibilities of both parties. For example, there could be an operational level agreement: I Between the IT service provider and a procurement department to obtain hardware in agreed times - I Between the service desk and a support group to provide incident resolution in agreed times. See also service level agreement.
325	operations bridge	nadzorni center	<i>(ITIL Service Operation)</i> A physical location where IT services and IT infrastructure are monitored and managed.
326	operations control	nadzor obratovanja	See IT operations control.
327	operations management	upravljanje obratovanja	See IT operations management.

#	Angleški pojem	Slovenski pojem	Angleški opis
328	opportunity cost	oportunitetni stroški	<i>(ITIL Service Strategy)</i> A cost that is used in deciding between investment choices. Opportunity cost represents the revenue that would have been generated by using the resources in a different way. For example, the opportunity cost of purchasing a new server may include not carrying out a service improvement activity that the money could have been spent on. Opportunity cost analysis is used as part of a decision-making process, but opportunity cost is not treated as an actual cost in any financial statement.
329	optimize	optimalizirati	Review, plan and request changes, in order to obtain the maximum efficiency and effectiveness from a process, configuration item, application etc.
330	organization	organizacija	A company, legal entity or other institution. The term is sometimes used to refer to any entity that has people, resources and budgets – for example, a project or business unit.
331	outcome	izid	The result of carrying out an activity, following a process, or delivering an IT service etc. The term is used to refer to intended results as well as to actual results. <i>See also</i> objective.
332	outsourcing	zunanje izvajanje	<i>(ITIL Service Strategy)</i> Using an external service provider to manage IT services. <i>See also</i> service sourcing.
333	overhead	posredni stroški	<i>See</i> indirect cost.
334	pain value analysis	vrednostna analiza škode	<i>(ITIL Service Operation)</i> A technique used to help identify the business impact of one or more problems. A formula is used to calculate pain value based on the number of users affected, the duration of the downtime, the impact on each user, and the cost to the business (if known).
335	Pareto principle	Paretovo načelo	<i>(ITIL Service Operation)</i> A technique used to prioritize activities. The Pareto principle says that 80% of the value of any activity is created with 20% of the effort. Pareto analysis is also used in problem management to prioritize possible problem causes for investigation.
336	partnership	partnerstvo	A relationship between two organizations that involves working closely together for common goals or mutual benefit. The IT service provider should have a partnership with the business and with third parties who are critical to the delivery of IT services. <i>See also</i> value network.
337	passive monitoring	pasivno spremljanje	<i>(ITIL Service Operation)</i> Monitoring of a configuration item, an IT service or a process that relies on an alert or notification to discover the current status. <i>See also</i> active monitoring.
338	pattern of business activity (PBA)	vzorec poslovne aktivnosti	<i>(ITIL Service Strategy)</i> A workload profile of one or more business activities. Patterns of business activity are used to help the IT service provider understand and plan for different levels of business activity. <i>See also</i> user profile.
339	percentage utilization	odstotek izkoriščenosti	<i>(ITIL Service Design)</i> The amount of time that a component is busy over a given period of time. For example, if a CPU is busy for 1,800 seconds in a one-hour period, its utilization is 50%.
340	performance	izvršitev	A measure of what is achieved or delivered by a system, person, team, process or IT service.
341	performance management	upravljanje izvršitve	Activities to ensure that something achieves its expected outcomes in an efficient and consistent manner.
342	pilot	vzorčna postavitve	<i>(ITIL Service Transition)</i> A limited deployment of an IT service, a release or a process to the live environment. A pilot is used to reduce risk and to gain user feedback and acceptance. <i>See also</i> change evaluation; test.
343	plan	načrt	A detailed proposal that describes the activities and resources needed to achieve an objective – for example, a plan to implement a new IT service or process. ISO/IEC 20000 requires a plan for the management of each IT service management process.

#	Angleški pojem	Slovenski pojem	Angleški opis
344	Plan-Do-Check-Act (PDCA)	načrtuj-izvedi-preveri-ukrepa	<i>(ITIL Continual Service Improvement)</i> A four-stage cycle for process management, attributed to Edward Deming. Plan-Do-Check-Act is also called the Deming Cycle. Plan – design or revise processes that support the IT services; Do – implement the plan and manage the processes; Check – measure the processes and IT services, compare with objectives and produce reports; Act – plan and implement changes to improve the processes.
345	planned downtime	načrtovani čas izpada	<i>(ITIL Service Design)</i> Agreed time when an IT service will not be available. Planned downtime is often used for maintenance, upgrades and testing. <i>See also</i> change window; downtime.
346	planning	načrtovanje	An activity responsible for creating one or more plans – for example, capacity planning.
347	policy	politika	Formally documented management expectations and intentions. Policies are used to direct decisions, and to ensure consistent and appropriate development and implementation of processes, standards, roles, activities, IT infrastructure etc.
348	portable facility	premični objekt	<i>(ITIL Service Design)</i> A prefabricated building, or a large vehicle, provided by a third party and moved to a site when needed according to an IT service continuity plan. <i>See also</i> fixed facility; recovery option.
349	post-implementation review (PIR)	pregled po uvedbi	A review that takes place after a change or a project has been implemented. It determines if the change or project was successful, and identifies opportunities for improvement.
350	practice	praksa	A way of working, or a way in which work must be done. Practices can include activities, processes, functions, standards and guidelines. <i>See also</i> best practice.
351	prerequisite for success (PFS)	predpogoj za uspeh	An activity that needs to be completed, or a condition that needs to be met, to enable successful implementation of a plan or process. It is often an output from one process that is a required input to another process.
352	pricing	določanje cene	<i>(ITIL Service Strategy)</i> Pricing is the activity for establishing how much customers will be charged.
353	PRINCE2®	PRINCE2®	<i>See</i> PProjects IN Controlled Environments.
354	priority	prioriteta	<i>(ITIL Service Operation)</i> <i>(ITIL Service Transition)</i> A category used to identify the relative importance of an incident, problem or change. Priority is based on impact and urgency, and is used to identify required times for actions to be taken. For example, the service level agreement may state that Priority 2 incidents must be resolved within 12 hours.
355	proactive monitoring	vnapijnjnje spremljanje	<i>(ITIL Service Operation)</i> Monitoring that looks for patterns of events to predict possible future failures. <i>See also</i> reactive monitoring.
356	proactive problem management	vnapijnjnje upravljanje problemov	<i>(ITIL Service Operation)</i> Part of the problem management process. The objective of proactive problem management is to identify problems that might otherwise be missed. Proactive problem management analyses incident records, and uses data collected by other IT service management processes to identify trends or significant problems.
357	problem	problem	<i>(ITIL Service Operation)</i> A cause of one or more incidents. The cause is not usually known at the time a problem record is created, and the problem management process is responsible for further investigation.
358	problem management	upravljanje problemov	<i>(ITIL Service Operation)</i> The process responsible for managing the lifecycle of all problems. Problem management proactively prevents incidents from happening and minimizes the impact of incidents that cannot be prevented.
359	problem record	zapis o problemu	<i>(ITIL Service Operation)</i> A record containing the details of a problem. Each problem record documents the lifecycle of a single problem.
360	procedure	postopek	A document containing steps that specify how to achieve an activity. Procedures are defined as part of processes. <i>See also</i> work instruction.

#	Angleški pojem	Slovenski pojem	Angleški opis
361	process	postopek	A structured set of activities designed to accomplish a specific objective. A process takes one or more defined inputs and turns them into defined outputs. It may include any of the roles, responsibilities, tools and management controls required to reliably deliver the outputs. A process may define policies, standards, guidelines, activities and work instructions if they are needed.
362	process control	nadzor procesa	The activity of planning and regulating a process, with the objective of performing the process in an effective, efficient and consistent manner.
363	process manager	skrbnik procesa	A role responsible for the operational management of a process. The process manager's responsibilities include planning and coordination of all activities required to carry out, monitor and report on the process. There may be several process managers for one process – for example, regional change managers or IT service continuity managers for each data centre. The process manager role is often assigned to the person who carries out the process owner role, but the two roles may be separate in larger organizations.
364	process owner	lastnik procesa	The person who is held accountable for ensuring that a process is fit for purpose. The process owner's responsibilities include sponsorship, design, change management and continual improvement of the process and its metrics. This role can be assigned to the same person who carries out the process manager role, but the two roles may be separate in larger organizations.
365	production environment	produksijsko okolje	<i>See</i> live environment.
366	profit centre	profitni center	<i>(ITIL Service Strategy)</i> A business unit that charges for services provided. A profit centre can be created with the objective of making a profit, recovering costs, or running at a loss. An IT service provider can be run as a cost centre or a profit centre.
367	pro-forma	predloga	A template or example document containing sample data that will be replaced with real values when these are available.
368	programme	program	A number of projects and activities that are planned and managed together to achieve an overall set of related objectives and other outcomes.
369	project	projekt	A temporary organization, with people and other assets, that is required to achieve an objective or other outcome. Each project has a lifecycle that typically includes initiation, planning, execution, and closure. Projects are usually managed using a formal methodology such as PROjects IN Controlled Environments (PRINCE2) or the Project Management Body of Knowledge (PMBOK). <i>See also</i> charter; project management office; project portfolio.
370	project charter	vzpostavitevni dokument projekta	<i>See</i> charter.
371	Project Management Body of Knowledge (PMBOK)	Vodnik po znanju projektnega vodenja, PMBOK	A project management standard maintained and published by the Project Management Institute. <i>See</i> www.pmi.org for more information. <i>See also</i> PROjects IN Controlled Environments (PRINCE2).
372	Project Management Institute (PMI)	Združenje za projektni management, PMI	A membership association that advances the project management profession through globally recognized standards and certifications, collaborative communities, an extensive research programme, and professional development opportunities. PMI is a not-for-profit membership organization with representation in many countries around the world. PMI maintains and publishes the Project Management Body of Knowledge (PMBOK). <i>See</i> www.pmi.org for more information. <i>See also</i> PROjects IN Controlled Environments (PRINCE2).
373	project management office (PMO)	projektna pisarna	<i>(ITIL Service Design)</i> <i>(ITIL Service Strategy)</i> A function or group responsible for managing the lifecycle of projects. <i>See also</i> charter; project portfolio.

#	Angleški pojem	Slovenski pojem	Angleški opis
374	project portfolio	portfelj projektov	<i>(ITIL Service Design)</i> <i>(ITIL Service Strategy)</i> A database or structured document used to manage projects throughout their lifecycle. The project portfolio is used to coordinate projects and ensure that they meet their objectives in a cost-effective and timely manner. In larger organizations, the project portfolio is typically defined and maintained by a project management office. The project portfolio is important to service portfolio management as new services and significant changes are normally managed as projects. <i>See also</i> charter.
375	projected service outage (PSO)	predvideni učinki izpada storitve	<i>(ITIL Service Transition)</i> A document that identifies the effect of planned changes, maintenance activities and test plans on agreed service levels.
376	Projects IN Controlled Environments (PRINCE2)	PRINCE2	The standard UK government methodology for project management. <i>See</i> www.prince-officialsite.com for more information. <i>See also</i> Project Management Body of Knowledge (PMBOK).
377	qualification	usposobljenost	<i>(ITIL Service Transition)</i> An activity that ensures that the IT infrastructure is appropriate and correctly configured to support an application or IT service. <i>See also</i> validation.
378	quality	kakovost	The ability of a product, service or process to provide the intended value. For example, a hardware component can be considered to be of high quality if it performs as expected and delivers the required reliability. Process quality also requires an ability to monitor effectiveness and efficiency, and to improve them if necessary. <i>See also</i> quality management system.
379	quality assurance (QA)	zagotavljanje kakovosti	<i>(ITIL Service Transition)</i> The process responsible for ensuring that the quality of a service, process or other service asset will provide its intended value. Quality assurance is also used to refer to a function or team that performs quality assurance. This process is not described in detail within the core ITIL publications. <i>See also</i> service validation and testing.
380	quality management system (QMS)	sistem upravljanja kakovosti	<i>(ITIL Continual Service Improvement)</i> The framework of policy, processes, functions, standards, guidelines and tools that ensures an organization is of a suitable quality to reliably meet business objectives or service levels. <i>See also</i> ISO 9000.
381	quick win	hitra zmaga	<i>(ITIL Continual Service Improvement)</i> An improvement activity that is expected to provide a return on investment in a short period of time with relatively small cost and effort. <i>See also</i> Pareto principle.
382	RACI	ZOPS (Zadolžen, Odgovoren, Posvetovan, Seznanjen)	<i>(ITIL Service Design)</i> A model used to help define roles and responsibilities. RACI stands for responsible, accountable, consulted and informed.
383	reactive monitoring	odzivno spremljanje	<i>(ITIL Service Operation)</i> Monitoring that takes place in response to an event. For example, submitting a batch job when the previous job completes, or logging an incident when an error occurs. <i>See also</i> proactive monitoring.
384	real charging	dejansko zaračunavanje	<i>(ITIL Service Strategy)</i> A charging policy where actual money is transferred from the customer to the IT service provider in payment for the delivery of IT services. <i>See also</i> notional charging.
385	reciprocal arrangement	vzajemni dogovor	<i>(ITIL Service Design)</i> A recovery option. An agreement between two organizations to share resources in an emergency – for example, high-speed printing facilities or computer room space.
386	record	zapis	A document containing the results or other output from a process or activity. Records are evidence of the fact that an activity took place and may be paper or electronic – for example, an audit report, an incident record or the minutes of a meeting.
387	recovery	obnova	<i>(ITIL Service Design)</i> <i>(ITIL Service Operation)</i> Returning a configuration item or an IT service to a working state. Recovery of an IT service often includes recovering data to a known consistent state. After recovery, further steps may be needed before the IT service can be made available to the users (restoration).

#	Angleški pojem	Slovenski pojem	Angleški opis
388	recovery option	možnost obnove	<i>(ITIL Service Design)</i> A strategy for responding to an interruption to service. Commonly used strategies are manual workaround, reciprocal arrangement, gradual recovery, intermediate recovery, fast recovery, and immediate recovery. Recovery options may make use of dedicated facilities or third-party facilities shared by multiple businesses.
389	recovery point objective (RPO)	ciljna točka obnove	<i>(ITIL Service Design)</i> <i>(ITIL Service Operation)</i> The maximum amount of data that may be lost when service is restored after an interruption. The recovery point objective is expressed as a length of time before the failure. For example, a recovery point objective of one day may be supported by daily backups, and up to 24 hours of data may be lost. Recovery point objectives for each IT service should be negotiated, agreed and documented, and used as requirements for service design and IT service continuity plans.
390	recovery time objective (RTO)	ciljni čas obnove	<i>(ITIL Service Design)</i> <i>(ITIL Service Operation)</i> The maximum time allowed for the recovery of an IT service following an interruption. The service level to be provided may be less than normal service level targets. Recovery time objectives for each IT service should be negotiated, agreed and documented. <i>See also</i> business impact analysis.
391	redundancy	podvojenost, odvečnost	<i>(ITIL Service Design)</i> Use of one or more additional configuration items to provide fault tolerance. The term also has a generic meaning of obsolescence, or no longer needed.
392	relationship	odnos	A connection or interaction between two people or things. In business relationship management, it is the interaction between the IT service provider and the business. In service asset and configuration management, it is a link between two configuration items that identifies a dependency or connection between them. For example, applications may be linked to the servers they run on, and IT services have many links to all the configuration items that contribute to that IT service.
393	relationship processes	procesi upravljanja odnosov	The ISO/IEC 20000 process group that includes business relationship management and supplier management.
394	release	izdaja	<i>(ITIL Service Transition)</i> One or more changes to an IT service that are built, tested and deployed together. A single release may include changes to hardware, software, documentation, processes and other components.
395	release and deployment management	upravljanje izdaj in postavitvev	<i>(ITIL Service Transition)</i> The process responsible for planning, scheduling and controlling the build, test and deployment of releases, and for delivering new functionality required by the business while protecting the integrity of existing services.
396	release identification	oznaka izdaje	<i>(ITIL Service Transition)</i> A naming convention used to uniquely identify a release. The release identification typically includes a reference to the configuration item and a version number – for example, Microsoft Office 2010 SR2.
397	release management	upravljanje izdaj	<i>See</i> release and deployment management.
398	release package	paket izdaje	<i>(ITIL Service Transition)</i> A set of configuration items that will be built, tested and deployed together as a single release. Each release package will usually include one or more release units.
399	release record	zapis o izdaji	<i>(ITIL Service Transition)</i> A record that defines the content of a release. A release record has relationships with all configuration items that are affected by the release. Release records may be in the configuration management system or elsewhere in the service knowledge management system.
400	release unit	enota izdaje	<i>(ITIL Service Transition)</i> Components of an IT service that are normally released together. A release unit typically includes sufficient components to perform a useful function. For example, one release unit could be a desktop PC, including hardware, software, licences, documentation etc. A different release unit may be the complete payroll application, including IT operations procedures and user training.
401	release window	okno za spremembe	<i>See</i> change window.

#	Angleški pojem	Slovenski pojem	Angleški opis
402	reliability	zanesljivost	<i>(ITIL Continual Service Improvement) (ITIL Service Design)</i> A measure of how long an IT service or other configuration item can perform its agreed function without interruption. Usually measured as MTBF or MTBSI. The term can also be used to state how likely it is that a process, function etc. will deliver its required outputs. <i>See also</i> availability.
403	remediation	povrnitev stanja	<i>(ITIL Service Transition)</i> Actions taken to recover after a failed change or release. Remediation may include back-out, invocation of service continuity plans, or other actions designed to enable the business process to continue.
404	repair	popravilo	<i>(ITIL Service Operation)</i> The replacement or correction of a failed configuration item.
405	request for change (RFC)	zahtevek za spremembo	<i>(ITIL Service Transition)</i> A formal proposal for a change to be made. It includes details of the proposed change, and may be recorded on paper or electronically. The term is often misused to mean a change record, or the change itself.
406	request fulfilment	reševanje zahtevkov	<i>(ITIL Service Operation)</i> The process responsible for managing the lifecycle of all service requests.
407	request model	model obravnave zahtevkov	<i>(ITIL Service Operation)</i> A repeatable way of dealing with a particular category of service request. A request model defines specific agreed steps that will be followed for a service request of this category. Request models may be very simple, with no requirement for authorization (e.g. password reset), or may be more complex with many steps that require authorization (e.g. provision of an existing IT service). <i>See also</i> request fulfilment.
408	requirement	zahteva	<i>(ITIL Service Design)</i> A formal statement of what is needed – for example, a service level requirement, a project requirement or the required deliverables for a process. <i>See also</i> statement of requirements.
409	resilience	odpornost	<i>(ITIL Service Design)</i> The ability of an IT service or other configuration item to resist failure or to recover in a timely manner following a failure. For example, an armoured cable will resist failure when put under stress. <i>See also</i> fault tolerance.
410	resolution	rešitev	<i>(ITIL Service Operation)</i> Action taken to repair the root cause of an incident or problem, or to implement a workaround. In ISO/IEC 20000, resolution processes is the process group that includes incident and problem management.
411	resolution processes	procesi reševanja	The ISO/IEC 20000 process group that includes incident and problem management.
412	resource	vir	<i>(ITIL Service Strategy)</i> A generic term that includes IT infrastructure, people, money or anything else that might help to deliver an IT service. Resources are considered to be assets of an organization. <i>See also</i> capability; service asset.
413	response time	odzivni čas	A measure of the time taken to complete an operation or transaction. Used in capacity management as a measure of IT infrastructure performance, and in incident management as a measure of the time taken to answer the phone, or to start diagnosis.
414	responsiveness	odzivnost	A measurement of the time taken to respond to something. This could be response time of a transaction, or the speed with which an IT service provider responds to an incident or request for change etc.
415	restoration of service	obnova storitve	<i>See</i> restore.
416	restore	obnoviti	<i>(ITIL Service Operation)</i> Taking action to return an IT service to the users after repair and recovery from an incident. This is the primary objective of incident management.
417	retire	umakniti	<i>(ITIL Service Transition)</i> Permanent removal of an IT service, or other configuration item, from the live environment. Being retired is a stage in the lifecycle of many configuration items.
418	return on assets (ROA)	donosnost sredstev	<i>(ITIL Service Strategy)</i> A measurement of the profitability of a business unit or organization. Return on assets is calculated by dividing the annual net income by the total value of assets. <i>See also</i> return on investment.

#	Angleški pojem	Slovenski pojem	Angleški opis
419	return on investment (ROI)	donosnost naložbe	(<i>ITIL Continual Service Improvement</i>) (<i>ITIL Service Strategy</i>) A measurement of the expected benefit of an investment. In the simplest sense, it is the net profit of an investment divided by the net worth of the assets invested. <i>See also</i> net present value; value on investment.
420	return to normal	nazaj v običajno obratovanje	(<i>ITIL Service Design</i>) The phase of an IT service continuity plan during which full normal operations are resumed. For example, if an alternative data centre has been in use, then this phase will bring the primary data centre back into operation, and restore the ability to invoke IT service continuity plans again.
421	review	pregled	An evaluation of a change, problem, process, project etc. Reviews are typically carried out at predefined points in the lifecycle, and especially after closure. The purpose of a review is to ensure that all deliverables have been provided, and to identify opportunities for improvement. <i>See also</i> change evaluation; post-implementation review.
422	rights	pravice	(<i>ITIL Service Operation</i>) Entitlements, or permissions, granted to a user or role – for example, the right to modify particular data, or to authorize a change.
423	risk	tveganje	A possible event that could cause harm or loss, or affect the ability to achieve objectives. A risk is measured by the probability of a threat, the vulnerability of the asset to that threat, and the impact it would have if it occurred. Risk can also be defined as uncertainty of outcome, and can be used in the context of measuring the probability of positive outcomes as well as negative outcomes.
424	risk assessment	ocena tveganj	The initial steps of risk management: analysing the value of assets to the business, identifying threats to those assets, and evaluating how vulnerable each asset is to those threats. Risk assessment can be quantitative (based on numerical data) or qualitative.
425	risk management	obvladovanje tveganj	The process responsible for identifying, assessing and controlling risks. Risk management is also sometimes used to refer to the second part of the overall process after risks have been identified and assessed, as in 'risk assessment and management'. This process is not described in detail within the core ITIL publications. <i>See also</i> risk assessment.
426	role	vloga	A set of responsibilities, activities and authorities assigned to a person or team. A role is defined in a process or function. One person or team may have multiple roles – for example, the roles of configuration manager and change manager may be carried out by a single person. Role is also used to describe the purpose of something or what it is used for.
427	root cause	izvor	(<i>ITIL Service Operation</i>) The underlying or original cause of an incident or problem.
428	root cause analysis (RCA)	analiza izvora	(<i>ITIL Service Operation</i>) An activity that identifies the root cause of an incident or problem. Root cause analysis typically concentrates on IT infrastructure failures. <i>See also</i> service failure analysis.
429	running costs	tekoči stroški	<i>See</i> operational costs.
430	Sarbanes-Oxley (SOX)	Sarbanes-Oxleyjev zakon	US law that regulates financial practice and corporate governance.
431	scalability	prilagodljivost	The ability of an IT service, process, configuration item etc. to perform its agreed function when the workload or scope changes.
432	scope	obseg	The boundary or extent to which a process, procedure, certification, contract etc. applies. For example, the scope of change management may include all live IT services and related configuration items; the scope of an ISO/IEC 20000 certificate may include all IT services delivered out of a named data centre.
433	second-line support	druga raven podpore	(<i>ITIL Service Operation</i>) The second level in a hierarchy of support groups involved in the resolution of incidents and investigation of problems. Each level contains more specialist skills, or has more time or other resources.
434	security	varnost	<i>See</i> information security management.
435	security management	upravljanje varnosti	<i>See</i> information security management.

#	Angleški pojem	Slovenski pojem	Angleški opis
436	security management information system (SMIS)	informacijski sistem za upravljanje varnosti	<i>(ITIL Service Design)</i> A set of tools, data and information that is used to support information security management. The security management information system is part of the information security management system. <i>See also</i> service knowledge management system.
437	security policy	politika informacijske varnosti	<i>See</i> information security policy.
438	separation of concerns (SoC)	razmejitev odgovornosti	An approach to designing a solution or IT service that divides the problem into pieces that can be solved independently. This approach separates what is to be done from how it is to be done.
439	server	strežnik	<i>(ITIL Service Operation)</i> A computer that is connected to a network and provides software functions that are used by other computers.
440	service	storitev	A means of delivering value to customers by facilitating outcomes customers want to achieve without the ownership of specific costs and risks. The term 'service' is sometimes used as a synonym for core service, IT service or service package. <i>See also</i> utility; warranty.
441	service acceptance criteria (SAC)	kriteriji za prevzem storitve	<i>(ITIL Service Transition)</i> A set of criteria used to ensure that an IT service meets its functionality and quality requirements and that the IT service provider is ready to operate the new IT service when it has been deployed. <i>See also</i> acceptance.
442	service analytics	analitika storitve	<i>(ITIL Service Strategy)</i> A technique used in the assessment of the business impact of incidents. Service analytics models the dependencies between configuration items, and the dependencies of IT services on configuration items.
443	service asset	sredstvo storitve	Any resource or capability of a service provider. <i>See also</i> asset.
444	service asset and configuration management (SACM)	upravljanje sredstev in konfiguracije storitev	<i>(ITIL Service Transition)</i> The process responsible for ensuring that the assets required to deliver services are properly controlled, and that accurate and reliable information about those assets is available when and where it is needed. This information includes details of how the assets have been configured and the relationships between assets. <i>See also</i> configuration management system.
445	service capacity management (SCM)	upravljanje zmogljivosti storitev	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> The sub-process of capacity management responsible for understanding the performance and capacity of IT services. Information on the resources used by each IT service and the pattern of usage over time are collected, recorded and analysed for use in the capacity plan. <i>See also</i> business capacity management; component capacity management.
446	service catalogue	katalog storitev	<i>(ITIL Service Design)</i> <i>(ITIL Service Strategy)</i> A database or structured document with information about all live IT services, including those available for deployment. The service catalogue is part of the service portfolio and contains information about two types of IT service: customer-facing services that are visible to the business; and supporting services required by the service provider to deliver customer-facing services. <i>See also</i> customer agreement portfolio; service catalogue management.
447	service catalogue management	upravljanje kataloga storitev	<i>(ITIL Service Design)</i> The process responsible for providing and maintaining the service catalogue and for ensuring that it is available to those who are authorized to access it.
448	service change	sprememba storitve	<i>See</i> change.
449	service charter	vzpostavitevni dokument storitve	<i>(ITIL Service Design)</i> <i>(ITIL Service Strategy)</i> A document that contains details of a new or changed service. New service introductions and significant service changes are documented in a charter and authorized by service portfolio management. Service charters are passed to the service design lifecycle stage where a new or modified service design package will be created. The term charter is also used to describe the act of authorizing the work required by each stage of the service lifecycle with respect to the new or changed service. <i>See also</i> change proposal; service portfolio; service catalogue.
450	service continuity management	upravljanje neprekinjenosti storitve	<i>See</i> IT service continuity management.

#	Angleški pojem	Slovenski pojem	Angleški opis
451	service contract	storitvena pogodba	<i>(ITIL Service Strategy)</i> A contract to deliver one or more IT services. The term is also used to mean any agreement to deliver IT services, whether this is a legal contract or a service level agreement. <i>See also</i> customer agreement portfolio.
452	service culture	storitvena kultura	A customer-oriented culture. The major objectives of a service culture are customer satisfaction and helping customers to achieve their business objectives.
453	service design	oblikovanje storitev	<i>(ITIL Service Design)</i> A stage in the lifecycle of a service. Service design includes the design of the services, governing practices, processes and policies required to realize the service provider's strategy and to facilitate the introduction of services into supported environments. Service design includes the following processes: design coordination, service catalogue management, service level management, availability management, capacity management, IT service continuity management, information security management, and supplier management. Although these processes are associated with service design, most processes have activities that take place across multiple stages of the service lifecycle. <i>See also</i> design.
454	service design package (SDP)	paket izoblikovane storitve	<i>(ITIL Service Design)</i> Document(s) defining all aspects of an IT service and its requirements through each stage of its lifecycle. A service design package is produced for each new IT service, major change or IT service retirement.
455	service desk	storitveni center	<i>(ITIL Service Operation)</i> The single point of contact between the service provider and the users. A typical service desk manages incidents and service requests, and also handles communication with the users.
456	service failure analysis (SFA)	analiza odpovedi storitve	<i>(ITIL Service Design)</i> A technique that identifies underlying causes of one or more IT service interruptions. Service failure analysis identifies opportunities to improve the IT service provider's processes and tools, and not just the IT infrastructure. It is a time-constrained, project-like activity, rather than an ongoing process of analysis.
457	service hours	delovni čas storitve	<i>(ITIL Service Design)</i> An agreed time period when a particular IT service should be available. For example, 'Monday–Friday 08:00 to 17:00 except public holidays'. Service hours should be defined in a service level agreement.
458	service improvement plan (SIP)	načrt izboljšav storitve	<i>(ITIL Continual Service Improvement)</i> A formal plan to implement improvements to a process or IT service.
459	service knowledge management system (SKMS)	sistem upravljanja znanja o storitvah	<i>(ITIL Service Transition)</i> A set of tools and databases that is used to manage knowledge, information and data. The service knowledge management system includes the configuration management system, as well as other databases and information systems. The service knowledge management system includes tools for collecting, storing, managing, updating, analysing and presenting all the knowledge, information and data that an IT service provider will need to manage the full lifecycle of IT services. <i>See also</i> knowledge management.
460	service level	raven storitve	Measured and reported achievement against one or more service level targets. The term is sometimes used informally to mean service level target.
461	service level agreement (SLA)	dogovor o ravni storitve	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> An agreement between an IT service provider and a customer. A service level agreement describes the IT service, documents service level targets, and specifies the responsibilities of the IT service provider and the customer. A single agreement may cover multiple IT services or multiple customers. <i>See also</i> operational level agreement.

#	Angleški pojem	Slovenski pojem	Angleški opis
462	service level management (SLM)	upravljanje ravni storitev	<i>(ITIL Service Design)</i> The process responsible for negotiating achievable service level agreements and ensuring that these are met. It is responsible for ensuring that all IT service management processes, operational level agreements and underpinning contracts are appropriate for the agreed service level targets. Service level management monitors and reports on service levels, holds regular service reviews with customers, and identifies required improvements.
463	service level package (SLP)	paket ravni storitve	See service option.
464	service level requirement (SLR)	zahtevana raven storitve	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> A customer requirement for an aspect of an IT service. Service level requirements are based on business objectives and used to negotiate agreed service level targets.
465	service level target	ciljna raven storitve	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> A commitment that is documented in a service level agreement. Service level targets are based on service level requirements, and are needed to ensure that the IT service is able to meet business objectives. They should be SMART, and are usually based on key performance indicators.
466	service lifecycle	življenjski krog storitve	An approach to IT service management that emphasizes the importance of coordination and control across the various functions, processes and systems necessary to manage the full lifecycle of IT services. The service lifecycle approach considers the strategy, design, transition, operation and continual improvement of IT services. Also known as service management lifecycle.
467	service maintenance objective (SMO)	cilj vzdrževanja storitve	<i>(ITIL Service Operation)</i> The expected time that a configuration item will be unavailable due to planned maintenance activity.
468	service management	upravljanje storitev	A set of specialized organizational capabilities for providing value to customers in the form of services.
469	service management lifecycle	upravljanje življenjskega kroga storitev	See service lifecycle.
470	service manager	skrbnik storitve	A generic term for any manager within the service provider. Most commonly used to refer to a business relationship manager, a process manager or a senior manager with responsibility for IT services overall.
471	service model	model storitve	<i>(ITIL Service Strategy)</i> A model that shows how service assets interact with customer assets to create value. Service models describe the structure of a service (how the configuration items fit together) and the dynamics of the service (activities, flow of resources and interactions). A service model can be used as a template or blueprint for multiple services.
472	service operation	obratovanje storitve	<i>(ITIL Service Operation)</i> A stage in the lifecycle of a service. Service operation coordinates and carries out the activities and processes required to deliver and manage services at agreed levels to business users and customers. Service operation also manages the technology that is used to deliver and support services. Service operation includes the following processes: event management, incident management, request fulfilment, problem management, and access management. Service operation also includes the following functions: service desk, technical management, IT operations management, and application management. Although these processes and functions are associated with service operation, most processes and functions have activities that take place across multiple stages of the service lifecycle. See also operation.
473	service option	možnost storitve	<i>(ITIL Service Design)</i> <i>(ITIL Service Strategy)</i> A choice of utility and warranty offered to customers by a core service or service package. Service options are sometimes referred to as service level packages.
474	service owner	lastnik storitve	<i>(ITIL Service Strategy)</i> A role responsible for managing one or more services throughout their entire lifecycle. Service owners are instrumental in the development of service strategy and are responsible for the content of the service portfolio. See also business relationship management.

#	Angleški pojem	Slovenski pojem	Angleški opis
475	service package	storitveni paket	<i>(ITIL Service Strategy)</i> Two or more services that have been combined to offer a solution to a specific type of customer need or to underpin specific business outcomes. A service package can consist of a combination of core services, enabling services and enhancing services. A service package provides a specific level of utility and warranty. Customers may be offered a choice of utility and warranty through one or more service options. <i>See also</i> IT service.
476	service pipeline	seznam storitev v pripravi	<i>(ITIL Service Strategy)</i> A database or structured document listing all IT services that are under consideration or development, but are not yet available to customers. The service pipeline provides a business view of possible future IT services and is part of the service portfolio that is not normally published to customers.
477	service portfolio	portfelj storitev	<i>(ITIL Service Strategy)</i> The complete set of services that is managed by a service provider. The service portfolio is used to manage the entire lifecycle of all services, and includes three categories: service pipeline (proposed or in development), service catalogue (live or available for deployment), and retired services. <i>See also</i> customer agreement portfolio; service portfolio management.
478	service portfolio management (SPM)	upravljanje portfelja storitev	<i>(ITIL Service Strategy)</i> The process responsible for managing the service portfolio. Service portfolio management ensures that the service provider has the right mix of services to meet required business outcomes at an appropriate level of investment. Service portfolio management considers services in terms of the business value that they provide.
479	service potential	potencial storitve	<i>(ITIL Service Strategy)</i> The total possible value of the overall capabilities and resources of the IT service provider.
480	service provider	ponudnik storitev	<i>(ITIL Service Strategy)</i> An organization supplying services to one or more internal customers or external customers. Service provider is often used as an abbreviation for IT service provider. <i>See also</i> Type I service provider; Type II service provider; Type III service provider.
481	service provider interface (SPI)	vmesnik ponudnika storitev	<i>(ITIL Service Strategy)</i> An interface between the IT service provider and a user, customer, business process or supplier. Analysis of service provider interfaces helps to coordinate end-to-end management of IT services.
482	service reporting	poročanje o storitvah	<i>(ITIL Continual Service Improvement)</i> Activities that produce and deliver reports of achievement and trends against service levels. The format, content and frequency of reports should be agreed with customers.
483	service request	zahtevek za storitev	<i>(ITIL Service Operation)</i> A formal request from a user for something to be provided – for example, a request for information or advice; to reset a password; or to install a workstation for a new user. Service requests are managed by the request fulfilment process, usually in conjunction with the service desk. Service requests may be linked to a request for change as part of fulfilling the request.
484	service sourcing	določanje storitvenih virov	<i>(ITIL Service Strategy)</i> The strategy and approach for deciding whether to provide a service internally, to outsource it to an external service provider, or to combine the two approaches. Service sourcing also means the execution of this strategy. <i>See also</i> insourcing; internal service provider; outsourcing.
485	service strategy	strategija storitev	<i>(ITIL Service Strategy)</i> A stage in the lifecycle of a service. Service strategy defines the perspective, position, plans and patterns that a service provider needs to execute to meet an organization's business outcomes. Service strategy includes the following processes: strategy management for IT services, service portfolio management, financial management for IT services, demand management, and business relationship management. Although these processes are associated with service strategy, most processes have activities that take place across multiple stages of the service lifecycle.

#	Angleški pojem	Slovenski pojem	Angleški opis
486	service transition	prehod storitve	<i>(ITIL Service Transition)</i> A stage in the lifecycle of a service. Service transition ensures that new, modified or retired services meet the expectations of the business as documented in the service strategy and service design stages of the lifecycle. Service transition includes the following processes: transition planning and support, change management, service asset and configuration management, release and deployment management, service validation and testing, change evaluation, and knowledge management. Although these processes are associated with service transition, most processes have activities that take place across multiple stages of the service lifecycle. <i>See also</i> transition.
487	service validation and testing	preverjanje ustreznosti in preizkus storitve	<i>(ITIL Service Transition)</i> The process responsible for validation and testing of a new or changed IT service. Service validation and testing ensures that the IT service matches its design specification and will meet the needs of the business.
488	service valuation	vrednotenje storitve	<i>(ITIL Service Strategy)</i> A measurement of the total cost of delivering an IT service, and the total value to the business of that IT service. Service valuation is used to help the business and the IT service provider agree on the value of the IT service.
489	serviceability	storitvenost	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> The ability of a third-party supplier to meet the terms of its contract. This contract will include agreed levels of reliability, maintainability and availability for a configuration item.
490	seven-step improvement process	proces izboljševanja v sedmih korakih	<i>(ITIL Continual Service Improvement)</i> The process responsible for defining and managing the steps needed to identify, define, gather, process, analyse, present and implement improvements. The performance of the IT service provider is continually measured by this process and improvements are made to processes, IT services and IT infrastructure in order to increase efficiency, effectiveness and cost effectiveness. Opportunities for improvement are recorded and managed in the CSI register.
491	shared service unit	skupna služba	<i>See</i> Type II service provider.
492	shift	izmena	<i>(ITIL Service Operation)</i> A group or team of people who carry out a specific role for a fixed period of time. For example, there could be four shifts of IT operations control personnel to support an IT service that is used 24 hours a day.
493	simulation modelling	simulacijsko modeliranje	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> A technique that creates a detailed model to predict the behaviour of an IT service or other configuration item. A simulation model is often created by using the actual configuration items that are being modelled with artificial workloads or transactions. They are used in capacity management when accurate results are important. A simulation model is sometimes called a performance benchmark. <i>See also</i> analytical modelling; modelling.
494	single point of contact	enotna stična točka	<i>(ITIL Service Operation)</i> Providing a single consistent way to communicate with an organization or business unit. For example, a single point of contact for an IT service provider is usually called a service desk.
495	single point of failure (SPOF)	kritična točka odpovedi	<i>(ITIL Service Design)</i> Any configuration item that can cause an incident when it fails, and for which a countermeasure has not been implemented. A single point of failure may be a person or a step in a process or activity, as well as a component of the IT infrastructure. <i>See also</i> failure.
496	SLAM chart	grafikon spremljanja dogovora o ravni storitev	<i>(ITIL Continual Service Improvement)</i> A service level agreement monitoring chart is used to help monitor and report achievements against service level targets. A SLAM chart is typically colour-coded to show whether each agreed service level target has been met, missed or nearly missed during each of the previous 12 months.
497	SMART	SMART (določnost, merljivost, izvedljivost, ustreznost, pravočasnost)	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Design)</i> An acronym for helping to remember that targets in service level agreements and project plans should be specific, measurable, achievable, relevant and time-bound.

#	Angleški pojem	Slovenski pojem	Angleški opis
498	snapshot	posnetek stanja	(<i>ITIL Continual Service Improvement</i>) (<i>ITIL Service Transition</i>) The current state of a configuration item, process or any other set of data recorded at a specific point in time. Snapshots can be captured by discovery tools or by manual techniques such as an assessment. <i>See also</i> baseline; benchmark.
499	software asset management (SAM)	upravljanje programskih sredstev	(<i>ITIL Service Transition</i>) The process responsible for tracking and reporting the use and ownership of software assets throughout their lifecycle. Software asset management is part of an overall service asset and configuration management process. This process is not described in detail within the core ITIL publications.
500	source	vir	<i>See</i> service sourcing.
501	specification	podroben opis	A formal definition of requirements. A specification may be used to define technical or operational requirements, and may be internal or external. Many public standards consist of a code of practice and a specification. The specification defines the standard against which an organization can be audited.
502	stakeholder	deležnik	A person who has an interest in an organization, project, IT service etc. Stakeholders may be interested in the activities, targets, resources or deliverables. Stakeholders may include customers, partners, employees, shareholders, owners etc. <i>See also</i> RACI.
503	standard	standard	A mandatory requirement. Examples include ISO/IEC 20000 (an international standard), an internal security standard for Unix configuration, or a government standard for how financial records should be maintained. The term is also used to refer to a code of practice or specification published by a standards organization such as ISO or BSI. <i>See also</i> guideline.
504	standard change	standardna sprememba	(<i>ITIL Service Transition</i>) A pre-authorized change that is low risk, relatively common and follows a procedure or work instruction – for example, a password reset or provision of standard equipment to a new employee. Requests for change are not required to implement a standard change, and they are logged and tracked using a different mechanism, such as a service request. <i>See also</i> change model.
505	standard operating procedures (SOP)	standardni izvedbeni postopek	(<i>ITIL Service Operation</i>) Procedures used by IT operations management.
506	standby	stanje pripravljenosti	(<i>ITIL Service Design</i>) Used to refer to resources that are not required to deliver the live IT services, but are available to support IT service continuity plans. For example, a standby data centre may be maintained to support hot standby, warm standby or cold standby arrangements.
507	statement of requirements (SOR)	specifikacija zahtev	(<i>ITIL Service Design</i>) A document containing all requirements for a product purchase, or a new or changed IT service. <i>See also</i> terms of reference.
508	status	status	The name of a required field in many types of record. It shows the current stage in the lifecycle of the associated configuration item, incident, problem etc.
509	status accounting	spremljanje stanja	(<i>ITIL Service Transition</i>) The activity responsible for recording and reporting the lifecycle of each configuration item.
510	storage management	upravljanje hrambe	(<i>ITIL Service Operation</i>) The process responsible for managing the storage and maintenance of data throughout its lifecycle.
511	strategic	strateško	(<i>ITIL Service Strategy</i>) The highest of three levels of planning and delivery (strategic, tactical, operational). Strategic activities include objective setting and long-term planning to achieve the overall vision.
512	strategic asset	strateško sredstvo	(<i>ITIL Service Strategy</i>) Any asset that provides the basis for core competence, distinctive performance or sustainable competitive advantage, or which allows a business unit to participate in business opportunities. Part of service strategy is to identify how IT can be viewed as a strategic asset rather than an internal administrative function.
513	strategy	strategija	(<i>ITIL Service Strategy</i>) A strategic plan designed to achieve defined objectives.

#	Angleški pojem	Slovenski pojem	Angleški opis
514	strategy management for IT services	strateško upravljanje storitev IT	<i>(ITIL Service Strategy)</i> The process responsible for defining and maintaining an organization's perspective, position, plans and patterns with regard to its services and the management of those services. Once the strategy has been defined, strategy management for IT services is also responsible for ensuring that it achieves its intended business outcomes.
515	super user	naduporabnik	<i>(ITIL Service Operation)</i> A user who helps other users, and assists in communication with the service desk or other parts of the IT service provider. Super users are often experts in the business processes supported by an IT service and will provide support for minor incidents and training.
516	supplier	dobavitelj	<i>(ITIL Service Design)</i> <i>(ITIL Service Strategy)</i> A third party responsible for supplying goods or services that are required to deliver IT services. Examples of suppliers include commodity hardware and software vendors, network and telecom providers, and outsourcing organizations. <i>See also</i> supply chain; underpinning contract.
517	supplier and contract management information system (SCMIS)	informatijski sistem za upravljanje dobaviteljev in pogodb	<i>(ITIL Service Design)</i> A set of tools, data and information that is used to support supplier management. <i>See also</i> service knowledge management system.
518	supplier management	upravljanje dobaviteljev	<i>(ITIL Service Design)</i> The process responsible for obtaining value for money from suppliers, ensuring that all contracts and agreements with suppliers support the needs of the business, and that all suppliers meet their contractual commitments. <i>See also</i> supplier and contract management information system.
519	supply chain	dobavna veriga	<i>(ITIL Service Strategy)</i> The activities in a value chain carried out by suppliers. A supply chain typically involves multiple suppliers, each adding value to the product or service. <i>See also</i> value network.
520	support group	skupina za podporo	<i>(ITIL Service Operation)</i> A group of people with technical skills. Support groups provide the technical support needed by all of the IT service management processes. <i>See also</i> technical management.
521	support hours	delovni čas podpore	<i>(ITIL Service Design)</i> <i>(ITIL Service Operation)</i> The times or hours when support is available to the users. Typically these are the hours when the service desk is available. Support hours should be defined in a service level agreement, and may be different from service hours. For example, service hours may be 24 hours a day, but the support hours may be 07:00 to 19:00.
522	supporting service	podporna storitev	<i>(ITIL Service Design)</i> An IT service that is not directly used by the business, but is required by the IT service provider to deliver customer-facing services (for example, a directory service or a backup service). Supporting services may also include IT services only used by the IT service provider. All live supporting services, including those available for deployment, are recorded in the service catalogue along with information about their relationships to customer-facing services and other CIs.
523	SWOT analysis	PSPN analiza (analiza prednosti, slabosti, priložnosti in nevarnosti)	<i>(ITIL Continual Service Improvement)</i> A technique that reviews and analyses the internal strengths and weaknesses of an organization and the external opportunities and threats that it faces. SWOT stands for strengths, weaknesses, opportunities and threats.
524	system	sistem	A number of related things that work together to achieve an overall objective. For example: A computer system including hardware, software and applications A management system, including the framework of policy, processes, functions, standards, guidelines and tools that are planned and managed together – for example, a quality management system A database management system or operating system that includes many software modules which are designed to perform a set of related functions.
525	system management	upravljanje sistemov	The part of IT service management that focuses on the management of IT infrastructure rather than process.
526	tactical	taktični	The middle of three levels of planning and delivery (strategic, tactical, operational). Tactical activities include the medium-term plans required to achieve specific objectives, typically over a period of weeks to months.

#	Angleški pojem	Slovenski pojem	Angleški opis
527	technical management	upravljanje tehnične podpore	<i>(ITIL Service Operation)</i> The function responsible for providing technical skills in support of IT services and management of the IT infrastructure. Technical management defines the roles of support groups, as well as the tools, processes and procedures required.
528	technical observation (TO)	tehnično opazovanje	<i>(ITIL Continual Service Improvement)</i> <i>(ITIL Service Operation)</i> A technique used in service improvement, problem investigation and availability management. Technical support staff meet to monitor the behaviour and performance of an IT service and make recommendations for improvement.
529	technical support	upravljanje tehnične podpore	See technical management.
530	tension metrics	soodvisne metrike	<i>(ITIL Continual Service Improvement)</i> A set of related metrics, in which improvements to one metric have a negative effect on another. Tension metrics are designed to ensure that an appropriate balance is achieved.
531	terms of reference (TOR)	referenčni pogoji	<i>(ITIL Service Design)</i> A document specifying the requirements, scope, deliverables, resources and schedule for a project or activity.
532	test	test	<i>(ITIL Service Transition)</i> An activity that verifies that a configuration item, IT service, process etc. meets its specification or agreed requirements. See also acceptance; service validation and testing.
533	test environment	testno okolje	<i>(ITIL Service Transition)</i> A controlled environment used to test configuration items, releases, IT services, processes etc.
534	third party	tretja oseba	A person, organization or other entity that is not part of the service provider's own organization and is not a customer – for example, a software supplier or a hardware maintenance company. Requirements for third parties are typically specified in contracts that underpin service level agreements. See also underpinning contract.
535	third-line support	tretja raven podpore	<i>(ITIL Service Operation)</i> The third level in a hierarchy of support groups involved in the resolution of incidents and investigation of problems. Each level contains more specialist skills, or has more time or other resources.
536	threat	grožnja	A threat is anything that might exploit a vulnerability. Any potential cause of an incident can be considered a threat. For example, a fire is a threat that could exploit the vulnerability of flammable floor coverings. This term is commonly used in information security management and IT service continuity management, but also applies to other areas such as problem and availability management.
537	threshold	prag	The value of a metric that should cause an alert to be generated or management action to be taken. For example, 'Priority 1 incident not solved within four hours', 'More than five soft disk errors in an hour', or 'More than 10 failed changes in a month'.
538	throughput	prepustnost	<i>(ITIL Service Design)</i> A measure of the number of transactions or other operations performed in a fixed time – for example, 5,000 e-mails sent per hour, or 200 disk I/Os per second.
539	total cost of ownership (TCO)	celotni stroški lastništva	<i>(ITIL Service Strategy)</i> A methodology used to help make investment decisions. It assesses the full lifecycle cost of owning a configuration item, not just the initial cost or purchase price. See also total cost of utilization.
540	total cost of utilization (TCU)	celotni stroški izkoriščenosti	<i>(ITIL Service Strategy)</i> A methodology used to help make investment and service sourcing decisions. Total cost of utilization assesses the full lifecycle cost to the customer of using an IT service. See also total cost of ownership.
541	total quality management (TQM)	celovito obvladovanje kakovosti	<i>(ITIL Continual Service Improvement)</i> A methodology for managing continual improvement by using a quality management system. Total quality management establishes a culture involving all people in the organization in a process of continual monitoring and improvement.

#	Angleški pojem	Slovenski pojem	Angleški opis
542	transaction	transakcija	A discrete function performed by an IT service – for example, transferring money from one bank account to another. A single transaction may involve numerous additions, deletions and modifications of data. Either all of these are completed successfully or none of them is carried out.
543	transfer cost	prenesen strošek	<i>(ITIL Service Strategy)</i> A cost type which records expenditure made on behalf of another part of the organization. For example, the IT service provider may pay for an external consultant to be used by the finance department and transfer the cost to them. The IT service provider would record this as a transfer cost.
544	transition	prehod	<i>(ITIL Service Transition)</i> A change in state, corresponding to a movement of an IT service or other configuration item from one lifecycle status to the next.
545	transition planning and support	načrtovanje in podpora prehodu	<i>(ITIL Service Transition)</i> The process responsible for planning all service transition processes and coordinating the resources that they require.
546	trend analysis	analiza trendov	<i>(ITIL Continual Service Improvement)</i> Analysis of data to identify time-related patterns. Trend analysis is used in problem management to identify common failures or fragile configuration items, and in capacity management as a modelling tool to predict future behaviour. It is also used as a management tool for identifying deficiencies in IT service management processes.
547	tuning	naravnavanje	The activity responsible for planning changes to make the most efficient use of resources. Tuning is most commonly used in the context of IT services and components. Tuning is part of capacity management, which also includes performance monitoring and implementation of the required changes. Tuning is also called optimization, particularly in the context of processes and other non-technical resources.
548	Type I service provider	ponudnik storitev tipa I	<i>(ITIL Service Strategy)</i> An internal service provider that is embedded within a business unit. There may be several Type I service providers within an organization.
549	Type II service provider	ponudnik storitev tipa II	<i>(ITIL Service Strategy)</i> An internal service provider that provides shared IT services to more than one business unit. Type II service providers are also known as shared service units.
550	Type III service provider	ponudnik storitev tipa III	<i>(ITIL Service Strategy)</i> A service provider that provides IT services to external customers.
551	underpinning contract (UC)	podizvajalska pogodba	<i>(ITIL Service Design)</i> A contract between an IT service provider and a third party. The third party provides goods or services that support delivery of an IT service to a customer. The underpinning contract defines targets and responsibilities that are required to meet agreed service level targets in one or more service level agreements.
552	unit cost	strošek enote	<i>(ITIL Service Strategy)</i> The cost to the IT service provider of providing a single component of an IT service. For example, the cost of a single desktop PC, or of a single transaction.
553	urgency	nujnost	<i>(ITIL Service Design)</i> <i>(ITIL Service Transition)</i> A measure of how long it will be until an incident, problem or change has a significant impact on the business. For example, a high-impact incident may have low urgency if the impact will not affect the business until the end of the financial year. Impact and urgency are used to assign priority.
554	usability	uporabnost	<i>(ITIL Service Design)</i> The ease with which an application, product or IT service can be used. Usability requirements are often included in a statement of requirements.
555	use case	primer uporabe	<i>(ITIL Service Design)</i> A technique used to define required functionality and objectives, and to design tests. Use cases define realistic scenarios that describe interactions between users and an IT service or other system.
556	user	uporabnik	A person who uses the IT service on a day-to-day basis. Users are distinct from customers, as some customers do not use the IT service directly.
557	user profile (UP)	profil uporabnika	<i>(ITIL Service Strategy)</i> A pattern of user demand for IT services. Each user profile includes one or more patterns of business activity.

#	Angleški pojem	Slovenski pojem	Angleški opis
558	utility	koristnost	<i>(ITIL Service Strategy)</i> The functionality offered by a product or service to meet a particular need. Utility can be summarized as 'what the service does', and can be used to determine whether a service is able to meet its required outcomes, or is 'fit for purpose'. The business value of an IT service is created by the combination of utility and warranty. <i>See also</i> service validation and testing.
559	validation	preverjanje ustreznosti	<i>(ITIL Service Transition)</i> An activity that ensures a new or changed IT service, process, plan or other deliverable meets the needs of the business. Validation ensures that business requirements are met even though these may have changed since the original design. <i>See also</i> acceptance; qualification; service validation and testing; verification.
560	value chain	vrednostna veriga	<i>(ITIL Service Strategy)</i> A sequence of processes that creates a product or service that is of value to a customer. Each step of the sequence builds on the previous steps and contributes to the overall product or service. <i>See also</i> value network.
561	value for money	cenovna primernost	An informal measure of cost effectiveness. Value for money is often based on a comparison with the cost of alternatives. <i>See also</i> cost benefit analysis.
562	value network	vrednostna mreža	<i>(ITIL Service Strategy)</i> A complex set of relationships between two or more groups or organizations. Value is generated through exchange of knowledge, information, goods or services. <i>See also</i> partnership; value chain.
563	value on investment (VOI)	vrednost naložbe	<i>(ITIL Continual Service Improvement)</i> A measurement of the expected benefit of an investment. Value on investment considers both financial and intangible benefits. <i>See also</i> return on investment.
564	variable cost	spremenljivi stroški	<i>(ITIL Service Strategy)</i> A cost that depends on how much the IT service is used, how many products are produced, the number and type of users, or something else that cannot be fixed in advance.
565	variance	odstopanje	The difference between a planned value and the actual measured value. Commonly used in financial management, capacity management and service level management, but could apply in any area where plans are in place.
566	verification	preverjanje skladnosti	<i>(ITIL Service Transition)</i> An activity that ensures that a new or changed IT service, process, plan or other deliverable is complete, accurate, reliable and matches its design specification. <i>See also</i> acceptance; validation; service validation and testing.
567	verification and audit	preverjanje skladnosti in presoja	<i>(ITIL Service Transition)</i> The activities responsible for ensuring that information in the configuration management system is accurate and that all configuration items have been identified and recorded. Verification includes routine checks that are part of other processes – for example, verifying the serial number of a desktop PC when a user logs an incident. Audit is a periodic, formal check.
568	version	različica	<i>(ITIL Service Transition)</i> A version is used to identify a specific baseline of a configuration item. Versions typically use a naming convention that enables the sequence or date of each baseline to be identified. For example, payroll application version 3 contains updated functionality from version 2.
569	vision	vizija	A description of what the organization intends to become in the future. A vision is created by senior management and is used to help influence culture and strategic planning. <i>See also</i> mission.
570	vital business function (VBF)	ključna poslovna funkcija	<i>(ITIL Service Design)</i> Part of a business process that is critical to the success of the business. Vital business functions are an important consideration of business continuity management, IT service continuity management and availability management.
571	vulnerability	ranljivost	A weakness that could be exploited by a threat – for example, an open firewall port, a password that is never changed, or a flammable carpet. A missing control is also considered to be a vulnerability.
572	warm standby	zmerno hitro okrevanje	<i>See</i> intermediate recovery.

#	Angleški pojem	Slovenski pojem	Angleški opis
573	warranty	jamstvo	<i>(ITIL Service Strategy)</i> Assurance that a product or service will meet agreed requirements. This may be a formal agreement such as a service level agreement or contract, or it may be a marketing message or brand image. Warranty refers to the ability of a service to be available when needed, to provide the required capacity, and to provide the required reliability in terms of continuity and security. Warranty can be summarized as 'how the service is delivered', and can be used to determine whether a service is 'fit for use'. The business value of an IT service is created by the combination of utility and warranty. <i>See also</i> service validation and testing.
574	work in progress (WIP)	v izvajanju	A status that means activities have started but are not yet complete. It is commonly used as a status for incidents, problems, changes etc.
575	work instruction	navodilo za delo	A document containing detailed instructions that specify exactly what steps to follow to carry out an activity. A work instruction contains much more detail than a procedure and is only created if very detailed instructions are needed.
576	work order	delovni nalog	A formal request to carry out a defined activity. Work orders are often used by change management and by release and deployment management to pass requests to technical management and application management functions.
577	workaround	nadomestna rešitev	<i>(ITIL Service Operation)</i> Reducing or eliminating the impact of an incident or problem for which a full resolution is not yet available – for example, by restarting a failed configuration item. Workarounds for problems are documented in known error records. Workarounds for incidents that do not have associated problem records are documented in the incident record.
578	workload	delovna obremenitev	The resources required to deliver an identifiable part of an IT service. Workloads may be categorized by users, groups of users, or functions within the IT service. This is used to assist in analysing and managing the capacity, performance and utilization of configuration items and IT services. The term is sometimes used as a synonym for throughput.